

弹簧式侧面真空端口
 弹簧式直接安装型
 快速接头型/螺纹型


精密型 常规型真空吸盘(组件)

弹簧式侧面真空端口


代码	类型	接管方式	吸盘材质	颜色
J-WES31	弹簧式侧面真空端口	快速接头型	丁腈橡胶NBR	黑色
J-WES32			导电性硅橡胶SE	黑色
J-WES33			氟橡胶F	灰色




盘径Ø2~4




盘径Ø6、8



盘径Ø10



盘径Ø15~50



视角标准：第一视角


型号	盘径d	B	D	M	L ₁	L ₂	L ₃	P	行程S	E ₁	E ₂	对边H ₁	对边H ₂	T	弹簧最大负载(N)	重量(g)
J-WES31 J-WES32 J-WES33	2	40	4	M8×0.75	4	24	13	10	3	16.7	12.5	10	8	2	0.9~1.9	13.5
	3															
	4															
	6															
	8	6		M14×1	11	38	20	16	6	20.1	18.5	17	12	4	4.0~7.1	48
	10															
	15															
	20															
	25														7.0~12.6	52
	30															
	40															
	50															
	6															
	8															

弹簧式直接安装型


代码	类型	接管方式	吸盘材质	颜色
J-WES36	弹簧式直接安装型	螺纹型	丁腈橡胶NBR	黑色
J-WES37			导电性硅橡胶SE	黑色
J-WES38			氟橡胶F	灰色




盘径Ø2~4





盘径Ø6、8



盘径Ø10



盘径Ø15~50



视角标准：第一视角

型号	盘径d	B	M	A	L ₁	L ₂	P	行程S	对边H ₁	对边H ₂	弹簧最大负载(N)	重量(g)
J-WES36 J-WES37 J-WES38	2	32	M10×1	9.5	4	22.5	14	3	12	—	2.3~3.9	14.5
	3											
	4											
	6											
	8	59	M14×1	11.7	11	43.3	19	5.8	17	12	7.9~15.0	59
	10											
	15											
	20											
	25											
	30											
	40											
	50											
	6											
	8											

弹簧式侧面真空端口

型号	盘径d	B
J-WES31	15	59.1
J-WES32	20	60.1

J-WES31—d15



优惠价	数量	1~29	30~
价格	100%	另行报价	

