

标准型 ▶
无肩型/带肩型


定位销用衬套

无肩型


代码	类型	材质		硬度	表面处理
		国标	相当		
YEU01	无肩型	标准型	GCr15	56HRC~ 淬火硬度HRC56~, 镀层硬度850HV~	— 镀硬铬, 镀层厚度3~5μm
YEU02					



YEU01



YEU02



6.3

① L尺寸5~6时, 在L/2位置有1道油槽。

视角标准: 第一视角

代码	型号		L	D1	D1公差		V	R
	代码	DH8			m6	g6		
YEU01 YEU02	5	+0.018 0	5 6 8 10 12 16	10	+0.015 +0.006	-0.005 -0.014	1.5	0.5
	6		6 8 10 12 16	12			2	
	8	+0.022 0	8 10 12 16 20	14	+0.018 +0.007	-0.006 -0.017	3	1
	10		10 12 16 20 25	16				
	12			18			4	1.2
	13	+0.027 0	16 20 25 30	22				
	15			25	+0.021 +0.008	-0.007 -0.020	4	1.5
	16		20 25 30 35	26				
	20	+0.033 0		30	+0.025 +0.009	-0.009 -0.025	4	2.0
	25			35				



请按图示订货

代码	型号	DH8	L
YEU01	5	+0.018 0	5 6 8 10 12 16
YEU02	6		6 8 10 12 16

YEU01—D5—L6



未税价(元)

优惠价	数量	1~4	5~
●	价格	100%	另行报价



① 无表面处理




① 有表面处理

带肩型


代码	类型	材质		硬度	表面处理
		国标	相当		
YEU01	带肩型	标准型	GCr15	56HRC~ 淬火硬度HRC56~, 镀层硬度850HV~	— 镀硬铬, 镀层厚度3~5μm
YEU02					



YEU01



YEU02



6.3

视角标准: 第一视角

代码	型号		L	D1	D1公差		V	R
	代码	DH8			m6	g6		
YEU01 YEU02	5	+0.018 0	8 10 12 16	10	+0.015 +0.006	-0.005 -0.014	1.5	0.5
	6			12			2	
	8	+0.022 0	8 10 12 16 20	14	+0.018 +0.007	-0.006 -0.017	3	1
	10			16				
	12		10 12 16 20 25	18			4	1.2
	13	+0.027 0	16 20 25 30	22				
	15			25	+0.021 +0.008	-0.007 -0.020	4	1.5
	16		20 25 30 35	26				
	20	+0.033 0		30	+0.025 +0.009	-0.009 -0.025	4	2.0
	25			35				



请按图示订货

代码	型号	DH8	L
YEU01	5	+0.022 0	8 10 12 16
YEU02	10		

YEU01—D8—L10



未税价(元)

优惠价	数量	1~4	5~
●	价格	100%	另行报价



① 无表面处理



① 有表面处理