


代码	类型		材质	
			国标	相当
BLM06	自锁型	粗牙	0Cr18Ni9	SUS304
BLM16		细牙		



型号		L	螺距	XM	圈数	安装前长度 (参考值)	外径		建议选用 钻头直径	
代码	M						min	max		
粗牙 BLM06	2	2	0.4	1M	3.2	0.95	2.55	2.8	2.1	
		3		1.5M	5.3	1.52				
		4		2M	7.4	2.49				
	2.5	5	0.45	2.5M	9.5	3.1	3.2	3.7	2.6	
				3M	11.6	3.7				
				1M	3.6	1.5				
		3	6	0.5	1.5M	5.9	2.05	3.7	4.35	3.1
					2M	8.2	2.76			
					2.5M	10.5	3.88			
	4	8	0.7	3M	12.8	5	5.05	5.6	4.2	
				1M	4.2	1.49				
				1.5M	6.8	2.68				
	5	10	0.8	2M	9.4	3.88	6.25	6.8	5.2	
				2.5M	12	4.7				
				3M	14.6	5.5				
	6	12	1.0	1M	4	2.18	7.4	7.95	6.2	
				1.5M	6.6	3.93				
				2M	9.1	5.03				
	8	16	1.25	2.5M	12.2	9.65	9.8	10.35	8.3	
				3M	14.9	12.07				
				1M	4.8	5.08				
	10	20	1.5	1.5M	7.7	8.08	11.95	12.5	10.4	
				2M	10.6	10.85				
				2.5M	13.5	14.09				
12	24	1.75	3M	16.4	16.3	14.3	15	12.4		
			1M	5	6.18					
			1.5M	8.1	9.9					
14	28	2.0	2M	11.2	14.83	16.65	17.35	14.5		
			2.5M	14.2	17.2					
			3M	17.3	20.82					
16	32	2.0	1M	5.3	7.04	18.9	19.4	16.5		
			1.5M	8.4	12.68					
			2M	11.6	17.04					
18	36	2.5	2.5M	14.8	21.51	21.3	22	18.6		
			3M	18	25.7					
			1M	5.4	9.2					
20	40	2.5	1.5M	8.7	14.04	23.55	24.4	20.6		
			2M	11.9	19.4					
			2.5M	15.2	23					
30	60	3.0	3M	18.5	26.6					
			1M	6.3	11.4					
			1.5M	10	16.57					

型号		L	螺距	XM	圈数	安装前长度 (参考值)	外径		建议选用 钻头直径	
代码	M						min	max		
粗牙 BLM06	22	22	2.5	1M	6.9	14	25.9	26.9	22.6	
		33		1.5M	11	22				
		44		2M	15	31				
	24	24	3.0	2.5M	19	40	28	29	24.8	
				3M	22.9	49				
				1M	6.3	17.6				
		27	48	3.0	1.5M	10	24.81	31.4	32.4	27.8
					2M	13.7	32.05			
					2.5M	17.4	39.29			
	30	72	3.5	3M	21.1	46.53	34.9	36.1	30.9	
				1M	7.2	20.79				
				1.5M	11.3	28.8				
	30	90	3.5	2M	15.4	36.81	34.9	36.1	30.9	
				2.5M	19.5	44.82				
				3M	23.6	52.83				

型号		L	螺距	XM	圈数	外径		建议选用 钻头直径
代码	M					min	max	
细牙 BLM16	8	8	1.0	1M	6.2	9.7	10.25	8.25
		12		1.5M	9.9			
		16		2M	13.7			
	10	10	1.25	2.5M	17.5	11.95	12.5	10.25
				3M	21.2			
				1M	8.1			
	12	12	1.25	2M	17.6	12.1	12.65	
				2.5M	22.3			
				3M	27			
	14	14	1.5	1M	6.1	14.3	15	
				1.5M	9.9			
				2M	13.6			
	16	16	1.5	2.5M	17.4	14.3	15	
				3M	21.2			
				1M	7.7			
	18	18	1.5	1.5M	12.2	14.3	15	
				2M	16.7			
				2.5M	21.3			
	20	20	1.5	3M	25.8	14.25	14.95	
				1M	5.9			
				1.5M	9.5			
	24	24	1.5	2M	13.2	16.55	17.25	14.25
				2M	16.3			
				2.5M	20.7			
28	28	1.5	3M	25	18.9	19.6	16.25	
			1M	8.7				
			1.5M	13.8				
32	32	1.5	2M	18.9	18.9	19.6	16.25	
			2.5M	23.9				
			3M	29				
40	40	2.0	1M	11.3	23.15	24	20.25	
			1.5M	17.7				
			2M	24				
45	45	2.0	2.5M	30.4				
			3M	36.8				
			1M	12.5				
60	60	2.0	1.5M	19.6	34.5	35.7	30.5	
			2M	26.5				
			2.5M	33.6				
90	90	3.0	3M	40.6				

① 圈数为钢丝螺纹套自然状态下的圈数，是以折断槽为起始位置计算，公差为±1/4圈。

粗牙

细牙



请按图示订货

代码	M	L
BLM06	2	3

BLM06—M2—L3

代码	M	L	螺距
BLM16	8	8	1.0

BLM16—M8—L12—1.0



未税价(元)

● 优惠价
数量 1~9 10~
价格 100% 另行报价



交货期

8