

高化学抗性型


直柱型/肩型

塑料滑动轴承


代码	类型	材质	使用温度
OBE05	直柱型	聚醚醚酮(PEEK)	-100°C~+250°C
OBE06	肩型	含润滑剂与特殊填充剂	

- 特点: 自润滑, 免维护, 耐高温, 高温高载荷下耐磨性较好, 化学抗性优异。
- 用途: 广泛温度应用范围和高压敏感性特点。
- 该产品为压配式衬套, 内径公差为压入座孔H7后公差, 压入后采用通止规进行测量(自由状态下请勿用卡尺进行测量)。
- 安装时保证H7座孔表面光滑、平整, 安装端倒角25°。禁止直接击打端面, 避免产品变形影响尺寸。


直柱型
OBE05



肩型
OBE06



推荐配套轴公差: h9



直柱型

型号	d	d公差	L	D	a	b
代码	d	d公差	L	D	a	b
3	3	+0.046 +0.006	5 6	4.5		
4	4		4 6	5.5		
5	5	+0.058 +0.010	5 8 10	7		0.3
6	6		4 6 8 10 15	8		
8	8	+0.071 +0.013	5 8 10 12 15	10		
10	10		6 8 10 12 15 20	12		0.5
12	12		6 8 10 12 15 20 25	14		
14	14		8 10 12 15 20 25	16		
15	15	+0.086 +0.016	10 15 20	17		
16	16		8 10 12 15 20 25	18	0.5	
18	18		15 20 25	20		0.8
20	20		10 15 20 25 30	23		
25	25	+0.104 +0.020	12 15 20 25 30	28		
30	30		20 25 30 40	34		
35	35		20 25 30 40 50	39		
40	40	+0.125 +0.025	20 30 40 50	44		1.2
45	45		30	50		
50	50		40 50	55		

肩型

型号		d公差	L	D	H	T	b
代码	d						
OBE06	3	+0.046 +0.006	5	4.5	7.5	0.75	0.3
	4		3 4 6	5.5	9.5		
	5	+0.058 +0.010	4 5	7	11		
	6		4 6 8 10	8	12		
	8	+0.071 +0.013	4 5.5 7.5 10 15	10	15	1	0.5
	10		5 6 7 8 9 10 12 15 17	12	18		
	12		5 6 7 10 12 15 17 20	14	20		
	14		10 12 17	16	22		
	15	+0.086 +0.016	5 9 12 17 20	17	23	0.8	
	16		6 9 12 17 20 25	18	24		
	18		9 12 17	20	26		
	20		7 11.5 16.5 21.5	23	30		1.5
	25	+0.104 +0.020	11.5 16.5 21.5	28	35		
	30		16 26 37	34	42	2	1.2
	35		9 16 26	39	47		
	40	+0.125 +0.025	14 30 40 50	44	52		
45		50	50	58			
	50		40	55	63		

直柱型

型号	d	d公差	L
代码	d	d公差	L
3	3	+0.046 +0.006	5 6
4	4	+0.058 +0.010	4 6

OBE05—d3—L5

优惠价

数量	1~9	10~
价格	100%	另行报价



未税价(元)



交货期	7
-----	---



请按图示订货