

六角螺母

薄型/加厚型



薄型

| 代码 | 类型 | 螺纹 | 材质 | | 表面处理 | 适用标准 | 强度等级 |
|-------|----|----|--------------|--------|------|------------------|------|
| | | | 国标 | 相当 | | | |
| TBK01 | 粗牙 | 薄型 | 0Cr18Ni9 | SUS304 | — | GB/T 6172.1-2000 | — |
| TBK02 | | | 0Cr17Ni12Mo2 | SUS316 | | | |
| TBK08 | | | 10B21 | SUS304 | | | |
| TBK07 | 细牙 | 薄型 | 0Cr18Ni9 | SUS304 | 发黑 | GB/T 6173-2000 | 10级 |
| TBK09 | | | 10B21 | SUS304 | | | 发黑 |

TBK01/02/07



TBK08/09



视角标准：第一视角

粗牙

| 型号 | M | 螺距 P | m | | S | | e |
|-------------------|-----|------|-------|-------|-------|-------|-------|
| | | | (max) | (min) | (max) | (min) | (min) |
| (SUS304) TBK01 | 2 | 0.4 | 1.2 | 0.95 | 4 | 3.82 | 4.32 |
| | 2.5 | 0.45 | 1.6 | 1.35 | 5 | 4.82 | 5.45 |
| | 3 | 0.5 | 1.8 | 1.55 | 5.5 | 5.32 | 6.01 |
| | 4 | 0.7 | 2.2 | 1.95 | 7 | 6.78 | 7.66 |
| | 5 | 0.8 | 2.7 | 2.45 | 8 | 7.78 | 8.79 |
| | 6 | 1 | 3.2 | 2.9 | 10 | 9.78 | 11.05 |
| | 8 | 1.25 | 4 | 3.7 | 13 | 12.73 | 14.38 |
| | 10 | 1.5 | 5 | 4.7 | 16 | 15.73 | 17.77 |
| | 12 | 1.75 | 6 | 5.7 | 18 | 17.73 | 20.03 |
| | 14 | 2 | 7 | 6.42 | 21 | 20.67 | 23.36 |
| | 16 | 2 | 8 | 7.42 | 24 | 23.67 | 26.75 |
| | 20 | 2.5 | 10 | 9.1 | 30 | 29.16 | 32.95 |
| | 24 | 3 | 12 | 10.9 | 36 | 35 | 39.55 |
| | 27 | 3 | 13.5 | 12.4 | 41 | 40 | 45.2 |
| 30 | 3.5 | 15 | 13.9 | 46 | 45 | 50.85 | |
| 42 | 4.5 | 21 | 19.7 | 65 | 63.1 | 71.3 | |
| (SUS316) TBK02 | 3 | 0.5 | 1.8 | 1.55 | 5.5 | 5.32 | 6.01 |
| | 4 | 0.7 | 2.2 | 1.95 | 7 | 6.78 | 7.66 |
| | 5 | 0.8 | 2.7 | 2.45 | 8 | 7.78 | 8.79 |
| | 6 | 1 | 3.2 | 2.9 | 10 | 9.78 | 11.05 |
| | 8 | 1.25 | 4 | 3.7 | 13 | 12.73 | 14.38 |
| | 10 | 1.5 | 5 | 4.7 | 16 | 15.73 | 17.77 |
| | 12 | 1.75 | 6 | 5.7 | 18 | 17.73 | 20.03 |
| | 14 | 2 | 7 | 6.42 | 21 | 20.67 | 23.36 |
| | 16 | 2 | 8 | 7.42 | 24 | 23.67 | 26.75 |
| | 20 | 2.5 | 10 | 9.1 | 30 | 29.16 | 32.95 |
| | 24 | 3 | 12 | 10.9 | 36 | 35 | 39.55 |
| | 27 | 3 | 13.5 | 12.4 | 41 | 40 | 45.2 |
| | 30 | 3.5 | 15 | 13.9 | 46 | 45 | 50.85 |
| | 42 | 4.5 | 21 | 19.7 | 65 | 63.1 | 71.3 |
| (10B21) TBK08 | 3 | 0.5 | 1.8 | 1.55 | 5.5 | 5.32 | 6.01 |
| | 4 | 0.7 | 2.2 | 1.95 | 7 | 6.78 | 7.66 |
| | 5 | 0.8 | 2.7 | 2.45 | 8 | 7.78 | 8.79 |
| | 6 | 1 | 3.2 | 2.9 | 10 | 9.78 | 11.05 |
| | 8 | 1.25 | 4 | 3.7 | 13 | 12.73 | 14.38 |
| | 10 | 1.5 | 5 | 4.7 | 16 | 15.73 | 17.77 |
| | 12 | 1.75 | 6 | 5.7 | 18 | 17.73 | 20.03 |
| | 14 | 2 | 7 | 6.42 | 21 | 20.67 | 23.36 |
| | 16 | 2 | 8 | 7.42 | 24 | 23.67 | 26.75 |
| | 20 | 2.5 | 10 | 9.1 | 30 | 29.16 | 32.95 |
| | 22 | 2.5 | 11 | 9.9 | 34 | 33 | 37.29 |
| | 24 | 3 | 12 | 10.9 | 36 | 35 | 39.55 |

细牙

| 型号 | M | 螺距 P | m | | S | | e |
|-------------------|-----|------|-------|-------|-------|-------|-------|
| | | | (max) | (min) | (max) | (min) | (min) |
| (SUS304) TBK07 | 6 | 0.75 | 3.2 | 2.9 | 10 | 9.78 | 11.05 |
| | 8 | 1 | 4 | 3.7 | 13 | 12.73 | 14.38 |
| | 10 | 1 | 5 | 4.7 | 16 | 15.73 | 17.77 |
| | 12 | 1.25 | 6 | 5.7 | 18 | 17.73 | 20.03 |
| | 16 | 1.5 | 8 | 7.42 | 24 | 23.67 | 26.75 |
| | 20 | 1.5 | 10 | 9.1 | 30 | 29.16 | 32.95 |
| | 22 | 1.5 | 11 | 9.9 | 34 | 33 | 37.29 |
| | 24 | 2 | 12 | 10.9 | 36 | 35 | 39.55 |
| | 8 | 1 | 4.1 | 3.9 | 13 | 12.73 | 14.38 |
| | 10 | 1 | 5 | 4.7 | 16 | 15.73 | 17.77 |
| (10B21) TBK09 | 8 | 1.25 | 6 | 5.7 | 18 | 17.73 | 20.03 |
| | 12 | 1.25 | 7 | 6.42 | 21 | 20.67 | 23.36 |
| | 12A | 1.25 | 7 | 6.42 | 21 | 20.67 | 23.36 |
| | 14 | 1.5 | 8 | 7.42 | 24 | 23.67 | 26.75 |
| | 16 | 1.5 | 9 | 8.42 | 27 | 26.16 | 29.56 |
| | 18 | 1.5 | 10 | 9.1 | 30 | 29.16 | 32.95 |
| | 20 | 2 | 11 | 9.9 | 34 | 33 | 37.29 |
| | 22 | 2 | 12 | 10.9 | 36 | 35 | 39.55 |
| | 24 | 2 | 12 | 10.9 | 36 | 35 | 39.55 |
| | 24A | 2 | 12 | 10.9 | 36 | 35 | 39.55 |



请按图示订货

| 代码 | 型号 |
|------------|-----|
| M | 2 |
| (TBK0) | 2.5 |
| (TBK0) | 3 |
| TBK01 — M3 | |



未税价(元)

| 数量 | 1~4 | 5~ |
|----|------|------|
| 价格 | 100% | 另行报价 |



交货期

7


加厚型

| 代码 | 类型 | 螺纹 | 材质 | | 表面处理 | 适用标准 |
|-------|-----|----|--------------|--------|------|----------------|
| | | | 国标 | 相当 | | |
| TBK31 | 加厚型 | 粗牙 | 45 | S45C | 镀锌 | GB/T 6175-2016 |
| TBK32 | | | 0Cr18Ni9 | SUS304 | | |
| TBK33 | | | 0Cr17Ni12Mo2 | SUS316 | | |

TBK31



TBK32/33



视角标准：第一视角

| 型号 | M | 螺距 P | m | | S | | e |
|-------------------|----|------|-------|-------|-------|-------|-------|
| | | | (max) | (min) | (max) | (min) | (min) |
| (S45C) TBK31 | 6* | 1 | 5.7 | 5.4 | 10 | 9.78 | 11.05 |
| (SUS304) TBK32 | 8 | 1.25 | 7.5 | 7.14 | 13 | 12.73 | 14.38 |
| (SUS304) TBK33 | 10 | 1.5 | 9.3 | 8.94 | 16 | 15.73 | 17.77 |
| (SUS316) TBK33 | 12 | 1.75 | 12 | 11.57 | 18 | 17.73 | 20.03 |
| (SUS316) TBK33 | 16 | 2 | 16.4 | 15.7 | 24 | 23.67 | 26.75 |
| (SUS316) TBK33 | 20 | 2.5 | 20.3 | 19 | 30 | 29.16 | 32.95 |
| (SUS316) TBK33 | 24 | 3 | 23.9 | 22.6 | 36 | 35 | 39.55 |



请按图示订货

| 代码 | 型号 |
|-------------|----|
| M | 6 |
| (TBK3) | 8 |
| (TBK3) | 10 |
| TBK31 — M10 | |



未税价(元)

| 数量 | 1~4 | 5~ |
|----|------|------|
| 价格 | 100% | 另行报价 |



交货期

7

① 带*规格仅适用于TBK32。