

# ISO标准矩形弹簧



## 中载荷弹簧(蓝色)

代码	类型	材质	最大压缩量
YSIM	中载荷型	SWOSC-V	L×37.5%

□ L尺寸公差

L	公差
89以下	±1
102以上	±1%

- ① 载荷(±10%)
- ① 直角度(3°以下)
- ① 负载(N)=弹簧常数(N/mm)×压缩量
- ① 理论使用次数: 30万次(L×25%为100万次)
- ① 弹簧颜色和圈数可能会因生产批次不同而异, 但产品性能均符合标准, 不影响使用!
- ① 参考标准 ISO 10243-2019



视角标准: 第一视角

型号		轴径 Dd	弹簧常数 N/mm	使用方法 30万次 F=L×37.5%		
代码	孔径D			长度L	Fmm	负载N
YSIM	10	5	16	9.4	150.4	
			32	13	156	
			38	11.9	14.2	169
			44	10.3	16.5	170
			51	8.9	19.1	170
			64	7.5	24	180
	76	6.2	28.5	176.7		
	305	1.6	114	182.4		
	25	30	9.4	282		
	32	24.8	12	297.6		
	38	21.4	14.2	303.9		
	44	18	16.5	297		
	12.5	6.3	51	15.5	19.1	296.1
	64		12.1	24	290.4	
	76		10.2	28.5	290.7	
	89		8.4	33.3	279.7	
	305		2.4	114	273.6	
	25		49.4	9.4	464.4	
	32	38.5	12	462		
	38	33.9	14.2	481.4		
	44	30	16.5	495		
	51	26.4	19.1	504.2		
	16	8	64	20.5	24	492
	76		17.8	28.5	507.3	
	89		15.2	33.3	506.2	
	102		13.5	38.2	515.7	
	305		4.3	114	490.2	
	25		98	9.4	921.2	
	32	72.6	12	871.2		
	38	56	14.2	795.2		
	44	47.5	16.5	783.8		
	51	41.7	19.1	796.5		
	64	32.3	24	775.2		
	76	25.1	28.5	715.4		
	20	10	89	22	33.3	732.6
	102		19.8	38.2	756.4	
	115		18.1	43.1	780.1	
	127		16.6	47.6	790.2	
	139		15.1	52.1	786.7	
	152		13.2	57	752.4	
	305	6.1	114	695.4		
	25	157	9.4	1476		
	32	118	12	1416		
	38	93	14.2	1321		
	44	80.8	16.5	1333		
	51	68.6	19.1	1310		
	64	53	24	1272		
	25	12.5	76	43.2	28.5	1231
89	38.2		33.3	1272		
102	33		38.2	1261		
115	28		43.1	1207		
127	25.9		47.6	1233		
139	23.2		52.1	1209		
152	20.8	57	1186			
178	17.8	66.7	1187			

型号		轴径 Dd	弹簧常数 N/mm	使用方法 30万次 F=L×37.5%		
代码	孔径D			长度L	Fmm	负载N
YSIM	25	12.5	203	15.8	76.1	1202
			305	10.2	114	1163
			38	185	14.2	2627
			44	158	16.5	2607
			51	134	19.1	2559
			64	99	24	2376
	76	80.5	28.5	2294		
	89	69.1	33.3	2301		
	102	58.8	38.2	2246		
	32	16	115	51.5	43.1	2220
	127		44.8	47.6	2132	
	139		42.3	52.1	2204	
	152		37.8	57	2155	
	178		32.5	66.7	2168	
	203		28.9	76.1	2199	
	254	22.2	95.2	2113		
	305	18.3	114	2086		
	51	182	19.1	3476		
	64	140	24	3360		
	76	108	28.5	3078		
	89	90.7	33.3	3020		
	102	81	38.2	3094		
	115	71.8	43.1	3095		
	40	20	127	62.7	47.6	2985
	139		57.5	52.1	2996	
	152		51.6	57	2941	
	178		44.1	66.7	2941	
	203		36.7	76.1	2793	
	254		30.1	95.2	2866	
	305	24.6	114	2804		
	64	209	24	5016		
	76	168	28.5	4788		
	89	140	33.3	4662		
	102	119	38.2	4546		
	115	106	43.1	4569		
	50	25	127	97	47.6	4617
	139		87	52.1	4533	
	152		80	57	4560	
	178		69.5	66.7	4636	
	203		59.8	76.1	4551	
	229		50.9	85.8	4367	
	254	46	95.2	4379		
	305	38.6	114	4400		
	76	320	28.5	9120		
	89	260	33.3	8658		
	102	221	38.2	8442		
	115	187	43.1	8060		
	63	38	127	168	47.6	7997
152	136		57	7752		
178	114		66.7	7604		
203	100		76.1	7610		
229	89.2		85.8	7653		
254	78.4		95.2	7464		
305	64.7	114	7376			

弹簧  
氮气  
弹簧

C4



代码	孔径D	长度L
YSIM	10	25
		32

请按图示订货 YSIM-D10-L25



● 优惠价  
数量 1~9 10~  
价格 100% 另行报价

未税价(元)



交货期

7