

机器人电缆


带屏蔽·1000万次

无尘电缆 大电品牌

代码	类型	屏蔽	护套材质	温度	颜色
ZLM02	无尘电缆	带屏蔽	PVC	105℃	黑色


适用环境

- 适用于低负载U型移动场合；
- 室内使用，5℃以下低温使用电线会变硬，影响移动使用寿命。



销售方式	每卷长度
卷	100m/卷

DRCK



视角标准：第一视角

型号	截面面积	长度	线规	导体结构	容许电流	电缆外径	推荐弯曲
代码	芯数	(mm ²)	(m)	(AWG)	(根/mm)	(mm)	半径(mm)
ZLM02	2					4.1	
	3				1.7	4.2	
	4					4.5	
	5				1.6	4.7	
	6	0.1		28	20/0.08	1.5	4.9
	8				(0.41)	1.4	5.4
	10					1.3	5.9
	12					1.2	6.5
	15					1.1	6.4
	20					1	6.9
	2					4.5	42
	3				2.6	4.6	
	4					4.9	
	5				2.4	5.1	40
	6	0.2		25	40/0.08	2.3	5.4
	8				(0.58)	2.1	6
	10					2	6.8
	12					1.9	7.4
	15					1.6	7.2
	20					1.5	7.8
ZLM02	2		100			4.7	
	3		(100米整卷销售)			4.9	
	4				3.3	5.2	
	5				3.1	5.5	40
	6	0.3		23	60/0.08	2.9	5.9
	8				(0.72)	2.7	6.6
	10					2.5	7.3
	12					2.4	8
	15					2.1	7.9
	20					1.9	8.5
	2					5	5.2
	3					5.5	
	4				4.8	5.8	46
	5				4.5	6.2	
	6	0.5		20	110/0.08	4.2	6.7
	8				(0.97)	3.9	7.5
	10					3.7	8.4
	12					3.5	9.3
	15					3.1	9
	20					2.8	9.9

型号	截面面积	长度	线规	导体结构	容许电流	电缆外径	推荐弯曲
代码	芯数	(mm ²)	(m)	(AWG)	(根/mm)	(mm)	半径(mm)
ZLM02	2					5.6	
	3				6.2	5.8	
	4				5.8	6.2	51
	5				5.4	6.7	
	6	0.75		19	150/0.08	5.1	7.2
	8				(1.13)	4.7	8.1
	10					4.4	9.1
	12					4.2	10
	15					3.7	9.8
	20					3.4	10.8
	2					6.4	65
	3				8.6	6.7	
	4				7.8	7.2	63
	5				7.2	7.7	
	6	1.25	100	17	7/33/0.08	6.8	8.3
	8		(100米整卷销售)		(1.50)	6.3	9.5
	10					6	10.7
	12					5.8	12
	15					5.1	11.7
	20					4.7	12.9
ZLM02	2					12.6	7.4
	3					12.3	7.8
	4	2		15	7/57/0.08	11.1	8.4
	6				(2.00)	9.8	9.8
	8					9.2	11.5
	10					8.7	13
	2					19	8.8
	3					18.1	9.3
	4	3.5		12	7/64/0.10	16.3	10.1
	6				(2.60)	14.6	12.1
	8					13.7	14.3
	10					13.1	16.4



请按图示订货

型号	截面面积	长度
代码	芯数	(m)
ZLM02	2	100
	3	(100米整卷销售)

ZLM02—3—0.1—100

技术参数

导体	镀锡软铜丝
额定电压	600V
耐电压	AC2000V/min
绝缘电阻	100MΩ·Km以上 (at20℃)

线芯颜色识别

AWG28~AWG23

序号	颜色	序号	颜色
1	黑	11	天蓝
2	白	12	桃
3	红	13	黑
4	绿	14	白
5	黄	15	红
6	棕	16	绿
7	蓝	17	黄
8	橙	18	棕
9	灰	19	蓝
10	紫	20	橙

AWG20~AWG12(1~4芯)

序号	颜色
1	黑
2	白
3	红
4	绿

AWG20~AWG12(5芯以上)

白色芯线带黑色数字编码