



代码	类型		材质		允许位移量	弹簧常数公差
			国标	相当		
YUTT	外径基准 不锈钢型	标准型	0Cr18Ni9	SUS304-WPB	L×(27~40)%	±10%
E-YUTT		经济型				
J-YUTT		进口型				



D尺寸公差		L尺寸公差	
D	公差	L	公差
10以下	0 -0.5	50以下	±1.5
12以上	0 -0.8	55以上	±2.5



- ① 压紧长度为参考值，制作时会有少许差异。
- ② 使用次数：100万次。
- ③ 带( )的L规格两端均未进行磨削加工。
- ④ 此系列产品因结构升级改进，产品尺寸略有变动，新旧款交替期间，出货时可能有不同款产品，均不影响使用。

代码	型号		d	压紧长度	F max	允许负载 Nmax	弹簧常数 N/mm
	D	L					
YUTT E-YUTT J-YUTT	3	(5)*	0.35	2.8	2	2.9	1.45
		(10)*	0.4	4.8	4	5.9	1.48
		(15)*	0.45	8.3	6	8.8	1.47
		(20)*					
		(25)	0.5	14	8	11.8	1.48
		(30)					
	4	(5)*	0.4	2.6	2	2.9	1.45
		(10)*	0.45	3.9	4	5.9	1.48
		(15)*	0.5	6	6	8.8	1.47
		(20)*	0.55	9.4	8	11.8	1.48
		(25)*	0.6	14.4	10	14.7	1.47
		(30)*					
5	(5)*	0.45	2.6	2	2.9	1.45	
	(10)*	0.5	3.6	4	5.9	1.48	
	(15)*	0.6	7.5	6	8.8	1.47	
	(20)*						
	(25)*	0.65	10.7	10	14.7	1.47	
	(30)*						
	(35)	0.7	15.4	14	20.6	1.47	
	(40)						
	6	(5)*	0.5	2.4	2	3.9	1.95
		(10)*	0.6	4.2	4	7.8	
		(15)*	0.7	7.4	6	11.8	1.97
		(20)*					
(25)*		0.75	10	8	15.7	1.96	
(30)*							
(35)*		0.8	13.6	10	19.6	1.96	
(40)							
(45)		0.85	17.5	14	27.5	1.96	
(50)							
(60)		0.9	23.4	18	35.3	1.96	
(70)							
8	(10)*	0.75	5.3	4	7.8	1.95	
	(15)*	0.9	10.4	8	11.8	1.97	
	(20)*						
	(25)*	10	19.6	10	23.5	1.96	
	(30)*						
	(35)*	1	17	14	27.5	1.96	
	(40)*						
	(45)	1.1	25.3	20	39.2	1.96	
	(50)						
	(60)	1.2	39.6	28	54.9	1.95	
	(70)						
	10	(10)*	0.85	5.1	4	7.8	1.95
(15)*		1	9.5	6	11.8	1.97	
(20)*							
(25)*		10	19.6	10	23.5	1.96	
(30)*							
(35)*		1.1	14.3	14	27.5	1.96	
(40)							
(45)		1.2	20.4	18	35.3	1.96	
(50)							
(60)		1.3	29.9	24	47.1	1.97	
(70)							
13		(10)*	1.4	43.4	24	47.1	1.97
	(15)*	1	5.75	6	11.8		
	(20)*	1.2	10.5	8	15.7	1.96	
	(25)*						
	(30)*	1.3	15	12	23.5	1.96	
	(35)*						
	(40)*	1.4	20.3	16	31.4	1.96	
	(45)						
	(50)	1.5	27.8	20	39.2	1.96	
	(60)						
	(70)	1.6	38.4	28	54.9	1.96	
	(80)						

代码	型号		d	压紧长度	F max	允许负载 Nmax	弹簧常数 N/mm
	D	L					
YUTT E-YUTT J-YUTT	16	15*	1.2	7.2	6	11.8	1.97
		20	1.3	9.1	10	19.6	1.96
		25					
		30	1.4	12.3	12	23.5	1.96
		35*					
		40	1.5	16.5	14	27.5	1.96
	45						
	50	1.6	21.6	18	35.3	1.96	
	60						
	70	1.7	28	24	47.1	1.96	
	80						
	20	20	1.8	36	28	54.9	1.96
25	1.7	10.6	8	31.4	3.93		
30							
35	1.8	12.6	10	39.2	3.92		
40							
45	2	19	16	62.8	3.93		
50							
60	2.2	27.5	24	94.1	3.92		
70							
80	2.4	40.8	32	125.5	3.92		

- ① 允许位移量Fmax：表示弹簧允许压缩的最大长度，超出此压缩量使用弹簧会缩短。
- ② 允许负载Nmax：表示压缩Fmax的负载，单位N。
- ③ 弹簧常数N/mm=(Nmax)/(Fmax)。
- ④ 经济型仅适用带\*号规格。

请按图示订货

型号			
代码	D	L	d
YUTT	3	5	0.35
E-YUTT	3	10	0.4

YUTT - D3 - L5

● 优惠价

数量	1~9	10~
价格	100%	另行报价

未税价(元)

交货期

1

① 经济型仅适用带\*号规格。