


成对双联角接触球轴承

组合型 • DB/DF/DT配对
P4精度


品牌	轴承类型 代码	轴承精度	后置代码	轴承材质		接触角(°)
				国标	相当	
HRB	7	P4	未标注: 内圈引导树脂保持架 TA: 外圈引导树脂保持架	GCr15	SUJ2	C: 15° AC: 25°




-DB(反面)




安装图




-DF(正面)





安装图



-DT(串联)



安装图



视角标准: 第一视角

型号			d	D	B	r ₁ (min)	r ₂ (min)	额定载荷 (KN)		极限转速 (r/min)		安装尺寸									重量 (kg) 参考	
DB配对	DF配对	DT配对						Cr(动)	Cor(静)	脂润滑	油润滑	DB			DF			DT				
												d _a (min)	D _a (max)	r _a (max)	d _a (min)	D _a (max)	r _a (max)	d _a (min)	D _a (max)	r _a (max)		
7001AC/P4DB-HRB	—	—	12	28	8	0.3	0.15	8.5	5.08	35000	47000	14	26.4	0.3	—	—	—	—	—	—	—	0.04
7202CTA/P4DB-HRB	7202CTA/P4DF-HRB	—	15	35	11	0.6	0.3	15	10.1	38000	56000	20	33	0.6	20	33	0.3	20	30	0.6	0.1	
7003ACTA/P4DB-HRB	—	—	17	35	10	0.3	0.1	11.9	8.34	32000	48000	19	33.4	0.3	—	—	—	—	—	—	—	0.08
7004C/P4DB-HRB	—	—	20	42	12	0.6	0.3	17.1	12	25000	34000	25	39.5	0.6	—	—	—	25	37	0.6	0.14	
—	—	7204AC/P4DT-HRB	20	42	14	1	0.6	22.7	15.7	19000	27000	26	42	1	26	41	0.3	26	41	1	0.2	
7005CTA/P4DB-HRB	—	—	25	47	12	0.6	0.3	20	16	27000	40000	30	45	0.6	—	—	—	30	42	0.6	0.16	
7206C/P4DB-HRB	—	—	30	62	16	1	0.6	37.4	29.6	14000	—	36	57	—	—	—	—	36	56	—	0.4	
7010CTA/P4DB-HRB	—	—	50	80	16	1	0.3	41	43.6	13000	—	56	78	1	—	—	—	57	83	1	0.52	
71918ACTA/P4DB-HRB	—	—	90	125	18	1.1	0.6	63.2	82.6	6800	11000	97	120	—	—	—	—	—	—	—	1.12	

1Kg=9.81N



请按图示订货

型号

7010CTA/P4DB-HRB
71918ACTA/P4DB-HRB



未税价(元)

● 优惠价

数量 1~9 10~
价格 100% 另行报价



交货期

7