


精密型 高耐热快速接头

直接头
弯接头
外螺纹

直接头

代码	类型	材质			表面处理
		主体	螺纹部	密封部材料	主体
J-XP51	外螺纹 直接头	黄铜	黄铜	FKM	镀镍



型号	代码	d	公称 型号	R	D	E	B	C ₁	C ₂	A	L	S	喷嘴直径	有效断面 (mm ²)	重量(g)
J-XP51	4	1	M5	M5	6	9.7	22.5	17.6	15	2.8	19.8	10	2.4	2	8
			1	R1/8			23.7			8	19.7		3	4.5	10
			M5	M5			24.4			2.8	21.6		2.4	2	12
	6	1	R1/8	R1/8	8	11.8	24.8	19.5	16.3	8	20.8	12	5	11	12
			2	R1/4			26.2			11	20.1		6	17	17
			1	R1/8			29.9	20.2	17.2	8	25.9	14	6	20	18
	8	2	R1/4	R1/4	10	13.7	28.6			11	22.6		7	19	19
			1	R1/8			32.8			8	28.8		6	23	30
			2	R1/4			32.3	23.2	19.5	11	26.3	17	8.5	35	27
	10	3	R3/8	R3/8	12	17.5	31.8			12	25.5		9	32	32
			3	R3/8			34.9			12	28.6		11	50	45
			4	R1/2			36.9	26.3	22.3	15	28.7	21	11		59



型号	代码	d	公称 型号	R
J-XP51	4	1	M5	M5
J-XP51-d4-M5		1	R1/8	R1/8




优惠价	数量	1~29	30~
●	价格	100%	另行报价

交货期	1
-----	---

弯接头

代码	类型	材质			表面处理
		主体	螺纹部	密封部材料	主体
J-XP71	外螺纹 弯接头	黄铜	黄铜	FKM	镀镍



型号	代码	d	公称 型号	R	D	A	B	L	P	C ₁	C ₂	E	S	喷嘴直径	有效断面 (mm ²)	重量(g)
J-XP71	4	1	M5	M5	6	3	19	20.8	9.7	17.6	15	20.5	10	1.8	1.5	15
			1	R1/8		8	22	22.8						2.5	3.5	17
			M5	M5		3	20.7	23.6						1.8	1.9	23
	6	1	R1/8	R1/8	8	8	23.7	25.6	11.8	19.4	16	23.3	12	4	9	25
			2	R1/4		11	26.7	26.6								29
			1	R1/8		8	25	27.9					14	6	16	32
	8	2	R1/4	R1/4	10	11	28	28.8	13.7	20.2	17	24.8				35
			1	R1/8		8	27.5	32.3								55
			2	R1/4		11	30.5	33.2	17.5	23.2	19.5	29.3	17	8	30	58
	10	3	R3/8	R3/8	12	12	31.5	33.9								58
			3	R3/8		12	32	36.1								92
			4	R1/2		15	35	37.2	20.8	26.3	23	33.4	21	9	39	103



型号	代码	d	公称 型号	R
J-XP71	4	1	M5	M5
J-XP71-d4-M5		1	R1/8	R1/8



优惠价	数量	1~29	30~
●	价格	100%	另行报价

交货期	1
-----	---

气动接头
D8