


标准型 全不锈钢快拧接头

直接头
内螺纹/外螺纹

内螺纹

代码	类型	材质
XES81	内螺纹 直接头	SUS316
XES84		SUS304




视角标准：第一视角

型号	公称型号	d	R	L ₁	L ₂	S ₁	S ₂	B
代码	D管外径	适用软管内径						
(SUS316) XES81	4	M5	2.5	M5	14.5	5	8	4
		1		Rc1/8	17.5	8		
		M5		M5	18.5	5	12	
	6	1	4	Rc1/8	21.5	8		6
		2		Rc1/4	23.5	10	12	
		3		Rc3/8	24.5	11	17	
	8	1	6	Rc1/8	22	8	14	
		2		Rc1/4	24	10	17	6.5
		3		Rc3/8	25	11	19	
	10	4		Rc1/2	27	13	24	
		1		Rc1/8	24	8	17	
		2		Rc1/4	26	10	19	7.5
(SUS304) XES84	10	3	8	Rc3/8	27	11	19	
		4		Rc1/2	29	13	24	
		2		Rc1/4	28	10	19	
	12	3	10	Rc3/8	29	11	24	10
		4		Rc1/2	31	13	24	
		1		Rc3/8	34	11	22	
	16	3	13	Rc3/8	34	11	22	12
		4		Rc1/2	36	13	24	

外螺纹

代码	类型	材质
XES01	外螺纹 直接头	SUS316
XES04		SUS304

① M5密封圈材质为FKM70。



视角标准：第一视角

型号	公称型号	d	R	L ₁	L ₂	S	B
代码	D管外径	适用软管内径					
(SUS316) XES01	4	M5	2.5	M5	18.1	4	8
		1		R1/8	21	7.5	10
		2		R1/4	23	9.5	14
	6	M5	4	M5	24	4	
		1		R1/8	25	7.5	12
		2		R1/4	27	9.5	14
	8	3	6	R3/8	28	10.5	17
		4		R1/2	30	12.5	21
		1		R1/8	25.5	7.5	14
	10	2	8	R1/4	27.5	9.5	17
		3		R3/8	28.5	10.5	21
		4		R1/2	30.5	12.5	21
(SUS304) XES04	10	1	8	R1/8	27.5	7.5	14
		2		R1/4	29.5	9.5	17
		3		R3/8		10.5	21
	12	4	10	R1/2	30.5	12.5	21
		1		R1/8		7.5	14
		2		R1/4	32.5	9.5	19
	16	3	13	R3/8	33.5	10.5	21
		4		R1/2	35.5	12.5	21
		1		R3/8	38.5	10.5	22
		2		R1/2	40.5	12.5	22



请按图示订货 XES01-D4-1

型号	公称型号
代码 D管外径	公称型号
XES01 4	2



未税价(元)

优惠价
数量 1~19 20~
价格 100% 另行报价



交货期
9