

成对双联角接触球轴承


组合型 · DB/DF配对 · 无密封圈
标准型 接触角25°




代码	类型	轴承类型 代码	轴承精度	轴承材质	接触角 (°)
BBQ	组合型	标准型	7	GB/T 307.1 5级 GCr15 SUJ2	25

① 出厂前未封入润滑脂，请在使用前封入。


-DB(反面)




■ 安装图



-DF(正面)



■ 安装图



型号 代码	轴承型号	组合形式	d	D	B	r (min)	r ₁ (min)	基本额定负载(组合) (KN)		极限转速rpm(组合) (参考)		安装尺寸						重量 kg (参考)
								Cr(动)	Cor(静)	脂润滑	油润滑	db(min)	da(max)	ra(max)	db(min)	da(max)	ra(max)	
BBQ	706	DB (反面)	6	17	6			2.46	0.98	10000	15000	8	15.6		8	15		0.006
	708		8	22	7	0.3	0.15	3.73	1.54	78000	120000	10	20.6	0.3	10	20	0.15	0.012
	7000		26	8				8.33	4.82	30000	40000	12.5	24.8		11.2	23.5		0.023
	7200		30	9	0.6	0.3		10.8	5.7	27600	36800	15	27.5	0.6	12.5	25	0.3	0.029
	7001		28	8	0.3	0.15		9.04	5.58	27000	36000	14.5	26.8	0.3	13.2	25.5	0.15	0.025
	7201		32	10	0.6	0.3		12.41	7.46	25200	33600	17	29.5	0.6	14.5	27	0.3	0.035
	7002		32	9	0.3	0.15		9.67	6.48	22800	30400	17.5	30.8	0.3	16.2	29.5	0.15	0.035
	7202		35	11	0.6	0.3		11.97	7.8	22200	29600	20	32.5	0.6	17.5	30	0.3	0.046
	7003		35	10	0.3	0.15		10.21	7.3	21000	28000	19.5	33.8	0.3	18.2	32.5	0.15	0.046
	7203		40	12	0.6	0.3		17.01	11.22	19200	25600	22	37.5		19.5	35		0.064
	7004		42	14				17.17	12.54	17400	23200	25	39.5	0.6	22.5	37	0.3	0.080
	7204		20	14	1	0.6		22.68	15.54	16200	21600	26	42	1	25	41	0.6	0.100
	7005		25	12	0.6	0.3		17.98	14.16	15000	20000	30	44.5	0.6	27.5	42	0.3	0.093
	7205		52	15				25.76	19.54	14400	19200	31	47		30	46		0.125
	7006		55	13				23.33	19.6	12600	16800	36	50		35	49	0.6	0.135
	7206		30	16				35.8	28.2	12000	16000		57			56		0.193
	7007		62	14				29.48	26.2	11000	15000	41				56	1	0.180
	7207		35	17	1.1			47.14	38.2			42	67		40	65		0.281
	7008		68	15	1			31.59	30.2	10000	14000	46	63		45	62	0.6	0.222
	7208		40	18	1.1	0.6		54.43	49.4			47	75	1		73		0.355
	7009		75	16	1			37.42	36.6	9000	12000	51	70		50	69	1	0.282
	7209		45	85	19	1.1		58.97	53.2	8200	11000	52	80			78		0.404
	7010		80	16	1			39.2	39.2	8400	11200	56	75		55	74	0.6	0.306
	7210		50	20				69.17	65	7500	10000	57			51	83		0.457
	7011		90	18	1.1			55.9	55.2			62	85		60		1	0.214
	7211		55	100	21	1.5	1	81.8	76.4	7200	9600	64	94	1.5	61	91	0.6	0.600
	7012	DF (正面)	95	18	1.1	0.6		59.9	62.8	7000	9300	67	90	1		88	1	0.478
	7212		60	110	22	1.5	1	94.3	92	6600	8800	69	104	1.5	66	101	0.6	0.765
	7013		100	18	1.1	0.6		63.7	70.8			72	95	1	70	93	1.1	0.509
	7213		65	120	23	1.5	1	93.5	94.2	5900	7900	74	114	1.5	67	111	0.6	0.962
	7014		110	20	1.1	0.6		76.6	86.6	6000	8000	77	105	1	75	103	1	0.705
	7214		70	125	24	1.5	1	117.5	121.2	5600	7500	79	119	1.5	76	116	0.6	1.090
	7015		115	20	1.1	0.6		78.6	92	5700	7600	82	110	1	80	108	1.1	0.745
	7215		75	130	25	1.5	1	117	123	5400	7200	84	124	1.5	81	121	0.6	1.170
	7016		125	22	1.1	0.6		89.9	105	5300	7000	87	120	1	85	118		0.994
	7216		80	140	26	2	1	143.7	156			90	134	2	86	130	1	1.390
	7017		130	22	1.1	0.6		92.2	111	5000		92	125	1	90	123	1.1	1.040
	7217		85	150	28	2	1	142.4	150.6			95	144	2	91	140	0.6	1.780
	7018		140	24	1.5	0.6		102.1	124.8			99	134	1.5		131		1.350
	7218		90	160	30	2	1	189.4	199.8	4400	5800	100	154	2	96	150	1	2.180
	7019		145	24	1.5			112.6	138.6	4500	6000	104	139	1.5	104	136	1.1	1.410
	7219		95	170	32	2.1	1.1	204.9	213.6	4100	5500	107	163	2	102	158	0.6	2.67
	7020		150	24	1.5	1		115.3	146.2	4300	5800	109		1.5	109	141		1.47
	7220		100	180	34	2.1	1.1	230.2	242.4	4000	5300	112	144		107	168	1	3.26
	7021		160	26	2	1		134.9	169.4	1694	5400	115	154		115	150	1.1	1.860
	7221		105	190	36	2.1	1.1	250.9	273.4	5000	117	183			112	178	0.6	3.79
	7022		170	28	2	1		159.9	202.2	2022	5200	120	164		120	160	1	2.3
	7222		110	200	38	2.1	1.1	271.8	305.8	3058	4700	122	193		117	188	1	4.45
	7024		180	28	2	1		171.9	221	2210	4800	130	174		130	170	1.1	2.47
	7224		120	215	40	2.1	1.1	306.5	367	3670		132	208		127	203	0.6	6.26
	7026		200	33	2	1		197.6	260	2600		140	194		140	190		3.73
	7226		130	230	40	3	1.1	318.3	399.6	3996	4100	144	223	2.5	137	216	1	7.15
	7028		210	33	2	1		202.5	276	3100	4200	150	204	2	150	200	1.1	3.96
	7228		140	250	42	3	1.1	366.9	485.2	2800	3800	154	243	2.5	147	236	0.6	8.78

① 1Kg=9.81N



型号	组合形式
代码 轴承型号	DB
BBQ 7000	DF



优惠价
数量 1~9
价格 100% 另行报价

