



# 碟形弹簧

## 标准型

| 代码    | 类型  | 材质     | 表面处理 | 最大压缩量 |
|-------|-----|--------|------|-------|
| FEN01 | 标准型 | 51CrV4 | 磷化黑  | h×75% |
| FEN02 |     | SUS304 | —    |       |
| FEN03 |     | 50CrV4 | 磷化黑  |       |

| 厚度t    | 负载容许差<br>(75%位移量时) |
|--------|--------------------|
| < 1.25 | -7.5%~+25%         |
| 1.25~3 | -7.5%~+15%         |
| > 3~6  | -5.0%~+10%         |
| > 6~15 | ±5%                |



### 标准型

| 代码    | 型号   | 厚度t  | d    | 全位移h | 总高度L | 负载F-h<br>(75%位移量) |
|-------|------|------|------|------|------|-------------------|
| FEN01 | 6*   | 0.3  | 3.2  | 0.15 | 0.45 | 119               |
|       | 8    | 0.3  | 4.2  | 0.25 | 0.55 | 118               |
|       | 10   | 0.4  | 5.2  | 0.3  | 0.7  | 209               |
|       | 12.5 | 0.5  | 6.2  | 0.35 | 0.85 | 293               |
|       | 14   | 0.5  | 7.2  | 0.4  | 0.9  | 279               |
|       | 16   | 0.6  | 8.2  | 0.45 | 1.05 | 410               |
|       | 18   | 0.7  | 9.2  | 0.5  | 1.2  | 566               |
|       | 20   | 0.8  | 10.2 | 0.55 | 1.35 | 748               |
|       | 22.5 | 1.1  | 11.2 | 0.7  | 1.6  | 862               |
|       | 25   | 1.5  | 12.2 | 0.9  | 2.05 | 1779              |
| FEN02 | 28   | 1.6* | 14.2 | 0.9  | 2.1  | 1703              |
|       | 31.5 | 1.8* | 16.3 | 0.9  | 2.15 | 1764              |
|       | 35.5 | 2    | 18.3 | 1    | 2.25 | 1567              |
|       | 40   | 2.25 | 20.4 | 1.15 | 2.65 | 1518              |
|       | 45   | 2.5  | 22.4 | 1.3  | 3.1  | 3950              |
|       | 50   | 3    | 25.4 | 1.4  | 3.4  | 4392              |
|       |      |      |      | 1.1  | 4.1  | 11976             |
|       |      |      |      | 0.8  | 1.8  | 1107              |
|       |      |      |      | 0.65 | 1.45 | 707               |
|       |      |      |      | 0.5  | 1.2  | 566               |

① 带\*规格仅适用于FEN01；带()规格仅适用于FEN02。  
② 荷重为参考值。

### 标准型

| 代码    | 型号   | 厚度t  | d    | 全位移h | 总高度L | 负载F-h<br>(75%位移量) |
|-------|------|------|------|------|------|-------------------|
| FEN03 | 8    | 0.2  | 4.2  | 0.25 | 0.45 | 39                |
|       | 10   | 0.3  | 5.2  | 0.3  | 0.55 | 58                |
|       | 12.5 | 0.4  | 6.2  | 0.35 | 0.75 | 81                |
|       | 14   | 0.5  | 7.2  | 0.4  | 0.9  | 813               |
|       | 16   | 0.6  | 8.2  | 0.45 | 1.05 | 1000              |
|       | 18   | 0.7  | 9.2  | 0.5  | 1.2  | 1250              |
|       | 20   | 0.8  | 10.2 | 0.55 | 1.35 | 1530              |
|       | 22.5 | 1.1  | 11.2 | 0.7  | 1.6  | 1950              |
|       | 25   | 1.5  | 12.2 | 0.9  | 2.05 | 2910              |
|       | 28   | 1.8  | 14.2 | 1    | 2.25 | 3660              |
| FEN03 | 31.5 | 2    | 16.3 | 1.15 | 2.65 | 4760              |
|       | 35.5 | 2.25 | 18.3 | 1.3  | 3.1  | 5995              |
|       | 40   | 2.5  | 20.4 | 1.4  | 3.4  | 7720              |
|       | 45   | 3    | 22.4 | 1.6  | 3.85 | 1890              |
|       | 50   | 3.5  | 25.4 | 1.8  | 4.2  | 24900             |
|       |      |      |      | 1.1  | 4.1  | 12000             |
|       |      |      |      | 0.8  | 1.8  | 1107              |
|       |      |      |      | 0.65 | 1.45 | 707               |
|       |      |      |      | 0.5  | 1.2  | 566               |
|       |      |      |      | 0.4  | 0.9  | 279               |

| 代码    | 型号  | 厚度t | d    | 全位移h | 总高度L | 负载F-h<br>(75%位移量) |
|-------|-----|-----|------|------|------|-------------------|
| FEN03 | 56  | 1.5 | 28.5 | 1.95 | 3.45 | 2620              |
|       | 63  | 2   | 31   | 2.35 | 4.15 | 4240              |
|       | 71  | 2.5 | 36   | 2.6  | 4.6  | 6730              |
|       | 80  | 3   | 41   | 2.95 | 5.2  | 10500             |
|       | 90  | 3.5 | 46   | 3.2  | 5.7  | 14200             |
|       | 100 | 4   | 51   | 3.5  | 6.2  | 18610             |
|       | 112 | 5   | 57   | 4.5  | 8    | 30000             |
|       | 125 | 5.5 | 64   | 5.1  | 11.1 | 37500             |
|       | 140 | 6   | 72   | 5.6  | 12.5 | 48000             |
|       | 160 | 7   | 82   | 6.5  | 14.5 | 70800             |
| FEN03 | 180 | 8   | 92   | 7.1  | 15.6 | 84600             |
|       | 200 | 9   | 102  | 7.8  | 17   | 119000            |
|       | 225 | 10  | 112  | 8.5  | 18.5 | 153000            |
|       | 250 | 11  | 127  | 9.5  | 20.5 | 209000            |
|       |     |     |      | 4.5  | 8    | 15100             |
|       |     |     |      | 3.5  | 6.2  | 8610              |
|       |     |     |      | 2.8  | 6.3  | 13100             |
|       |     |     |      | 2.2  | 8.2  | 48000             |
|       |     |     |      | 1.7  | 6.7  | 33700             |
|       |     |     |      | 1.4  | 4.9  | 15000             |

② 荷重为参考值。



| 型号    | 厚度t |
|-------|-----|
| FEN01 | 10  |
| FEN02 | 0.5 |

FEN01-D8-t0.4



| 数量 | 1~99 | 100~ |
|----|------|------|
| 价格 | 100% | 另行报价 |

