



# 防水型 圆形连接器

## 后螺母插座 SA系列 威浦品牌



系列	类型	接插方式	材质			防护等级
			外壳 铝 (阳极氧化)	绝缘体 热塑塑料PPS	接触件 铜(镀金)	
SA系列	后螺母插座	推入式 快速锁紧				IP67 (连接后)



安装开孔尺寸

尺寸表

系列	D <sub>1</sub>	L	D <sub>2</sub>	L <sub>1</sub>	T(max)	M	D	H
SA6	7.8	12.9	10.2			M6×0.5	6	5.7
SA8	9.4	12.7	12.8	7.3	2	M8×0.5	8	7.7
SA10	11	19.8	14.8	12.5		M10×0.75	10	9.5
SA12	13.8	20	18	11.2	3.5	M12×0.75	12	11.5
SA16	18.3	22.1	22.8	13.1	4	M16×0.75	16	15.5
SA20	21.6	23.3	26.8	14.5		M20×1	20	19.5
SA24	25.3	24	30		4.5	M24×1.5	24	23.5
SA28	29.8	23.8	34.6	14		M28×1	28	27.5



视角标准：第一视角

### 插针

型号	颜色	配合直径	芯数	适配插头
				电缆插头
SA612P2			2	SA610S2
SA612P3		6	3	SA610S3
SA612P4			4	SA610S4
SA612P5			5	SA610S5
SA812P2		8	2	SA810S2
SA812P3			3	SA810S3
SA812P4			4	SA810S4
SA812P6			6	SA810S6
SA812P8			8	SA810S8
SA1012P2		10	2	SA1010S2
SA1012P3			3	SA1010S3
SA1012P4			4	SA1010S4
SA1012P5			5	SA1010S5
SA1212P2		12	2	SA1210S2
SA1212P3			3	SA1210S3
SA1212P4			4	SA1210S4
SA1212P5			5	SA1210S5
SA1212P6			6	SA1210S6
SA1212P7			7	SA1210S7
SA1212P9			9	SA1210S9
SA1612P2		16	2	SA1610S2
SA1612P3			3	SA1610S3
SA1612P4			4	SA1610S4
SA1612P5			5	SA1610S5
SA1612P7			7	SA1610S7
SA1612P9			9	SA1610S9
SA1612P10			10	SA1610S10
SA2012P2		20	2	SA2010S2
SA2012P3	B(黑色)		3	SA2010S3
SA2012P4	S(银色)		4	SA2010S4
SA2012P5			5	SA2010S5
SA2012P6			6	SA2010S6
SA2012P7			7	SA2010S7
SA2012P8			8	SA2010S8
SA2012P9			9	SA2010S9
SA2012P12			12	SA2010S12
SA2012P15			15	SA2010S15
SA2412P2		24	2	SA2410S2
SA2412P3			3	SA2410S3
SA2412P4			4	SA2410S4
SA2412P9			9	SA2410S9
SA2412P10			10	SA2410S10
SA2412P12			12	SA2410S12
SA2412P19			19	SA2410S19
SA2812P2		28	2	SA2810S2
SA2812P3			3	SA2810S3
SA2812P4			4	SA2810S4
SA2812P7			7	SA2810S7
SA2812P8			8	SA2810S8
SA2812P9			9	SA2810S9
SA2812P10			10	SA2810S10
SA2812P12			12	SA2810S12
SA2812P16			16	SA2810S16
SA2812P17			17	SA2810S17
SA2812P20			20	SA2810S20
SA2812P24			24	SA2810S24
SA2812P26			26	SA2810S26
SA2812P35			35	SA2810S35

### 插孔

型号	颜色	配合直径	芯数	适配插头
				电缆插头
SA612S2			2	SA610P2
SA612S3		6	3	SA610P3
SA612S4			4	SA610P4
SA612S5			5	SA610P5
SA812S2		8	2	SA810P2
SA812S3			3	SA810P3
SA812S4			4	SA810P4
SA812S6			6	SA810P6
SA812S8			8	SA810P8
SA1012S2		10	2	SA1010P2
SA1012S3			3	SA1010P3
SA1012S4			4	SA1010P4
SA1012S5			5	SA1010P5
SA1212S2		12	2	SA1210P2
SA1212S3			3	SA1210P3
SA1212S4			4	SA1210P4
SA1212S5			5	SA1210P5
SA1212S6			6	SA1210P6
SA1212S7			7	SA1210P7
SA1212S9			9	SA1210P9
SA1612S2		16	2	SA1610P2
SA1612S3			3	SA1610P3
SA1612S4			4	SA1610P4
SA1612S5			5	SA1610P5
SA1612S7			7	SA1610P7
SA1612S9			9	SA1610P9
SA1612S10			10	SA1610P10
SA2012S2		20	2	SA2010P2
SA2012S3	B(黑色)		3	SA2010P3
SA2012S4	S(银色)		4	SA2010P4
SA2012S5			5	SA2010P5
SA2012S6			6	SA2010P6
SA2012S7			7	SA2010P7
SA2012S8			8	SA2010P8
SA2012S9			9	SA2010P9
SA2012S12			12	SA2010P12
SA2012S15			15	SA2010P15
SA2412S2		24	2	SA2410P2
SA2412S3			3	SA2410P3
SA2412S4			4	SA2410P4
SA2412S9			9	SA2410P9
SA2412S10			10	SA2410P10
SA2412S12			12	SA2410P12
SA2412S19			19	SA2410P19
SA2812S2		28	2	SA2810P2
SA2812S3			3	SA2810P3
SA2812S4			4	SA2810P4
SA2812S7			7	SA2810P7
SA2812S8			8	SA2810P8
SA2812S9			9	SA2810P9
SA2812S10			10	SA2810P10
SA2812S12			12	SA2810P12
SA2812S16			16	SA2810P16
SA2812S17			17	SA2810P17
SA2812S20			20	SA2810P20
SA2812S24			24	SA2810P24
SA2812S26			26	SA2810P26
SA2812S35			35	SA2810P35

### 技术参数

接插方式	推入式快速锁紧
接线方式	焊接
接插次数	500次
温度范围	-40°C~+85°C



请按图示订货 SA611P2 - B

型号	颜色
SA611P2	B(黑色)
SA611P4	S(银色)