


60°锥面密封过渡接头

英制BSP螺纹 直接头

英制BSP螺纹-外螺纹-60°锥面密封

代码	类型	材质
WSB36	外螺纹	碳钢
WSB37		SUS304





视角标准：第一视角

型号		M	A	L	S
WSB36 WSB37	04	G1/4"×19	12	30	19
	08	G1/2"×14	16	42	27
	10	G5/8"×14	17.5	45	30
	12	G3/4"×14	18.5	48	32
	16	G1"×11	20.5	55.5	41

英制BSP螺纹-外螺纹-60°锥面密封和带O型圈密封

代码	类型	材质
WSB38	外螺纹	碳钢
WSB39		SUS304




视角标准：第一视角

型号		M	A	B	L	S
WSB38 WSB39	04	G1/4"×19	12	11	10	31
	08	G1/2"×14	16	14	14	41
	12	G3/4"×14	18.5	15.5	15.5	46
	16	G1"×11	20.5	18	18	53
	20	G1.1/4"×11	20.5	20	20	58.5

英制BSP螺纹-内外螺纹

代码	类型	材质
WSB40	内外螺纹	碳钢
WSB41		SUS304





视角标准：第一视角

型号		M	A	B	L	S
WSB40 WSB41	04	G1/4"×19	12	5.5	29	19
	08	G1/2"×14	16	7.5	40	27
	10	G5/8"×14	17.5	9.5	42	30
	12	G3/4"×14	18.5	10.9	44.5	32
	16	G1"×11	20.5	11.7	50	41

一端英制BSP螺纹-一端英制BSPT螺纹-外螺纹

代码	类型	材质
WSB42	外螺纹	碳钢
WSB43		SUS304



视角标准：第一视角

型号		M	N	A	B	L	S
WSB42 WSB43	04	G1/4"×19	R1/4"×19	12	14.5	32	19
	08	G1/2"×14	R1/2"×14	16	20	45	27
	12	G3/4"×14	R3/4"×14	18.5	20	48.5	32
	16	G1"×11	R1"×11	20.5	25.5	58	41
	20	G1.1/4"×11	R1.1/4"×11	20.5	26.5	62	50

英制BSP螺纹-外螺纹-60°锥面密封

型号		M
WSB36	04	G1/4"×19
WSB37	08	G1/2"×14

请按图示订货

WSB36-04



优惠价
数量 1~19 20~
价格 100% 另行报价

未税价(元)



交货期
5

