金属垫圈

○帯螺栓孔型


l	代码	类型	材	表面处理	
		突坐	国标	相当	表固处理
l	UAS01				_
l	UAS02		45	S45C	发黑
l	UAS03	带螺栓孔型			无电解镀镍
l	UAS07		0Cr18Ni9	SUS304	
l	UAS08		LY11	A2017	本色阳极氧化








① 如对防锈有要求,请优先选用不锈钢材质或无电解镀镍产品。











型号		V	Q	Т	d	适用
代码	D	最小单位0.1	最小单位0.1	最小单位0.5	u	螺钉
	20	2.0~6.0	10.0~13.0		3.3	M3
	25	2.0~10.0	10.0~17.0		3.3	IVIO
UAS01 UAS02	30	2.0~10.0	12.0~20.0			
UAS03	35	2.0~16.0	12.0~25.0	1.0~12.0	4.3	M4
UAS07 UAS08	40	2.0~20.0	12.0~30.0			
	50	2.0~22.0	14.0~35.0		5.3	M5
	60	2.0~28.0	14.0~40.0		5.5	IVIS



可选加工







◯ 可选加工

		V	0	TA	可洗加丁代码	
代码 D		4		. 33	31231121013	
UAS01	UAS01 20 UAS02 25		10.0~13.0	1 (5-13.0	RCD)	
UAS02	25	2.0~10.0	10. ~7.0	1.00-10.0	100	
UAS01-D25-V10-Q17-T10-FC3						







◎ 形状选择型

П						
	代码	孝型	材质		表面处理	
	I CII-J	突至	国标	相当	衣山火连	
	UAU01				1 - 10	
	UAU02	形状选择型	45	S45C	发黑	
	UAU03	//////////////////////////////////////			无电解镀镍	
	UAU07		0Cr18Ni9	SUS304	_	













如对防锈有要求,请优先选用不锈钢材质或无电解镀镍产品。

形状选择: A










<u>L</u>	6.3/	
_		
	T±0.1	

视角标准:第一视角

型号		D	V ^N	X	T
代码	形状选择	最小单位0.5	最小单位0.5	最小单位0.1	最小单位0.1
UAU01 UAU02 UAU03 UAU07	ABCDE	10.0~20.0	3.0~40.0	3.0~48.0 (A形不选择)	3.0~12.0











轴垫