


# 圆形 径向锁紧螺母

代码	类型	形状	精度	端面偏差	材质		热处理	表面处理
					国标	相当		
E-BKE01	经济型	径向锁紧型 三槽	6H	0.002~0.005	45	S45C	28~32HRC	发黑



特点：锁紧螺母的锁紧方向为两点或三点式径向锁定，适用于设计或装配上受限，无法使用其他产品的情况。  
 由于热处理工艺表面可能会出现少许发红。



视角标准：第一视角

代码	型号	公称尺寸	螺距	D	H	g	t	d	n-m	扭紧力矩 (NM)
E-BKE01	M6		0.75	16				12		
			1.0					13		
	M8		0.75					15		
			1.0	3-M4	3.5					
	M9		0.75							
			1.0	20			16			
	M10		1.5							
			1.0	25			21			
	M12		1.25							
			1.0	28			23			
	M14		1.25							
			1.0	30	10	4	2	25	3-M5	4.5
	M15		1.5							
			1.0	32				27		
	M16		1.5							
			1.0	35				30		
	M17		1.0							
			1.0	45	12	5		40		
	M18		1.5							
			1.0	50				45		
	M20		1.5							
			1.0	52				46		8
	M22		1.5							
			1.0	58				52	3-M6	
	M24		1.0							
			1.5	65				59		
	M25		1.5							
			1.0	70	14	6		64		
	M30		1.5							
			1.0	75				3		
	M32		1.5							
			1.0	76	16	7		69		18
M33		1.5								
		1.0	80				73	3-M8		
M35		1.5								
		1.0	85				78			
M40		1.5								
		1.0	92				84			
M44		1.5								
		1.0	98	18	8		3.5	90		
M45		1.5								
		1.0	105				96			
M50		1.5								
		1.0								
M52		1.5								
		1.0								
M54		1.5								
		1.0								
M55		1.5								
		1.0								
M58		1.5								
		1.0								
M60		1.5								
		1.0								
M65		1.5								
		1.0								
M70		1.5								
		1.0								
M75		1.5								
		1.0								
M80		1.5								
		1.0								



请按图示订货

型号		
代码	公称尺寸	螺距
E-BKE01	M6	0.75
	M8	1

E-BKE01—M6—0.75



未税价(元)

● 优惠价

数量	1~9	10~
价格	100%	另行报价




交货期

5



Example 使用示例



用于锁紧机床主轴与零件间的配合，便于拆卸。主要用于机电设备、传送装置的锁紧等。