


圆形 ▶ 锁紧螺母
径向锁紧型

代码	类型	形状	精度	端面偏摆	材质		热处理	表面处理
					国标	相当		
E-BKE01	经济型 径向 锁紧型	三槽	6H	0.002~0.005	45	S45C	28~32HRC	发黑

特点：锁紧螺母的锁紧方向为两点或三点式径向锁定，适用于设计或装配上受限，无法使用其他产品的情况。
① 由于热处理工艺表面可能会出现少许发红。



三槽
E-BKE01



视角标准：第一视角

型号	螺距	D	H	g	t	d	n-m	锁紧力矩 (NM)
M6	0.75						12	
	1.0	16						
M8	0.75						13	
	1.0							
M9	0.75						15	
	1.0	18						
M10	1.5	8	3	1.6		3-M4	3.5	
	1.0							
M12	1.25	20					16	
	1.0							
M14	1.25	25					21	
	1.0							
M15	1.5							
	1.0							
M16	1.0						23	
	1.5	28		2				
M17	1.0							
M18	1.5	30	10	4		3-M5	4.5	
	1.0							
M20	1.5						27	
	1.0							
M22		35					30	
M24								
M25		38			2.5		33	
M30		45	12	5				
M32	1.5	50					8	
M35		52						
M40		58				3-M6		
M44		65					59	
M45								
M50	1.5		14	6				
	2.0	70					64	
M52								
M54	1.5				3			
M55								
	1.5	75						
	2.0						69	
M58	1.5	76	16	7			18	
M60		80					73	
M65		85				3-M8	78	
M70	2.0	92					84	
M75		98	18	8	3.5		90	
M80		105					96	



请按图示订货

型号		
代码	公称尺寸	螺距
E-BKE01	M6	0.75
		1

E-BKE01—M6—0.75



未税价(元)

优惠价		
数量	1~9	10~
价格	100%	另行报价



交货期
5



Example
使用示例



① 用于锁紧机床主轴与零件间的配合，便于拆卸。主要用于机电设备、传送装置的锁紧等。