



带橡胶密封圈型

圆弧型 接触角30°

双列角接触球轴承

代码	类型	后置代码	轴承精度	轴承材质		接触角 (°)
				国标	相当	
LR...-2RS	圆弧型	2RS(双面带橡胶密封圈接触式)	GB/T 307.1 0级	GCr15	SUJ2	30°



视角标准：第一视角

型号	d	D	B	基本额定负载		容许转速rpm (参考)	安装尺寸		重量(kg) 参考
				Cr(动)KN	Cor(静)KN		db	r (min)	
LR5000-2RS	10	28	12	4.75	2.85	9000	13.5	0.3	0.03
LR5200-2RS		32	14	6.8	4.05	8000	15.4	0.6	0.07
LR5300-2RS		37	19	10.8	7.05	7000	19.4	1	0.08
LR5001-2RS	12	30	12	4.95	3.1	8500	15.5	0.3	0.03
LR5201-2RS		35	15.9	8.6	5.1	7500	17.1	0.6	0.08
LR5301-2RS		42	19	11.3	7.1	6500	21.1	1	0.12
LR5002-2RS	15	35	13	6.5	4.1		20.4	0.3	0.05
LR5202-2RS		40	15.9	9.8	6.2	7000	20	0.6	0.11
LR5302-2RS		47	19	14.6	9.2		24	1	0.15
LR5003-2RS	17	40	14	7.7	5.2	6000	21.6	0.3	0.07
LR5203-2RS		47	17.5	12.6	8.2	5500	22.5	0.6	0.17
LR5303-2RS		52	22.2	17.2	11.1	4700	23.5	1	0.21
LR5004-2RS	20	47	16	11.5	7.7	5500	25.2	0.6	0.12
LR5204-2RS		52	20.6	15.8	10.5	5000	26.5	1	0.23
LR5304-2RS		62	22.2	21.1	14.5	4500	29	1.1	0.34

1Kg $\approx$ 9.81N

请按图示订货 LR5000-2RS

型号	d	D	B
LR5000-2RS	10	28	12
LR5200-2RS		32	14



未税价(元)

优惠价		
数量	1~19	20~
价格	100%	另行报价



交货期
6

关节轴承

E7