


经济型防滑脚杯

固定调节型 重载型

| 代码 | 类型 | 材质 | | 表面处理 | |
|---------|-------|--------|--------|--------|--------|
| | | 底座 | 螺杆 | 底座 | 螺杆 |
| E-WAD81 | 带防滑槽型 | S45C | S45C | 电泳(黑色) | 电泳(黑色) |
| E-WAD82 | | | | 镀锌 | 镀锌 |
| E-WAD83 | | | | 镀铬 | 镀铬 |
| E-WAD84 | | SUS304 | SUS304 | — | — |

☑ 高性价比脚杯，经济实用型。

⚠ 由于市面上钢材位为5mm一个梯度，且存在公差，因此车制底座公差-2~0mm均为合理范围。



视角标准：第一视角

| 型号 代码 | D | M | L | 螺距 | H | S | V | V ₁ | 承载 (Kg) | 参考重量 (Kg/pcs) | |
|----------|---------|-----|------|------|------|----|----|----------------|------------|------------------|------|
| E-WAD81 | 40 | 8 | 50 | 1.25 | 14 | 6 | 6 | 300 | 0.2 | 0.2 | |
| | | | 75 | | | | | | 0.21 | | |
| | | | 100 | | | | | | 0.22 | | |
| | | 125 | 0.22 | | | | | | | | |
| | | 150 | 0.23 | | | | | | | | |
| | | 175 | 0.24 | | | | | | | | |
| | E-WAD82 | 12 | 100 | 100 | 1.75 | 19 | 8 | 10 | 450 | 0.24 | 0.25 |
| | | | | 125 | | | | | | 0.26 | |
| | | | | 150 | | | | | | 0.26 | |
| | | | 175 | 0.45 | | | | | | | |
| | | | 200 | 0.46 | | | | | | | |
| | | | 225 | 0.47 | | | | | | | |
| E-WAD83 | 60 | 16 | 100 | 2 | 18 | 24 | 10 | 700 | 0.47 | 0.49 | |
| | | | 125 | | | | | | 0.51 | | |
| | | | 150 | | | | | | 0.49 | | |
| | | 175 | 0.51 | | | | | | | | |
| | | 200 | 0.53 | | | | | | | | |
| | | 225 | 0.55 | | | | | | | | |
| | E-WAD84 | 20 | 100 | 100 | 2.5 | 30 | 13 | 16 | 800 | 0.47 | 0.49 |
| | | | | 125 | | | | | | 0.51 | |
| | | | | 150 | | | | | | 0.53 | |
| | | | 175 | 0.55 | | | | | | | |
| | | | 200 | 0.57 | | | | | | | |
| | | | 225 | 0.57 | | | | | | | |
| E-WAD82 | 70 | 16 | 100 | 2 | 23 | 30 | 13 | 850 | 0.55 | 0.57 | |
| | | | 125 | | | | | | 0.55 | | |
| | | | 150 | | | | | | 0.57 | | |
| | | 175 | 0.55 | | | | | | | | |
| | | 200 | 0.57 | | | | | | | | |
| | | 225 | 0.59 | | | | | | | | |
| | E-WAD81 | 24 | 100 | 100 | 3 | 36 | 16 | 19 | 900 | 0.61 | 0.62 |
| | | | | 125 | | | | | | 0.64 | |
| | | | | 150 | | | | | | 0.64 | |
| | | | 175 | 0.74 | | | | | | | |
| | | | 200 | 0.76 | | | | | | | |
| | | | 225 | 0.78 | | | | | | | |
| E-WAD82 | 80 | 20 | 100 | 2.5 | 23 | 30 | 13 | 850 | 0.8 | 0.82 | |
| | | | 125 | | | | | | 0.82 | | |
| | | | 150 | | | | | | 0.78 | | |
| | | 175 | 0.8 | | | | | | | | |
| | | 200 | 0.82 | | | | | | | | |
| | | 225 | 0.84 | | | | | | | | |
| | E-WAD83 | 24 | 100 | 100 | 3 | 36 | 16 | 19 | 900 | 0.89 | 0.87 |
| | | | | 125 | | | | | | 0.89 | |
| | | | | 150 | | | | | | 0.87 | |
| | | | 175 | 0.89 | | | | | | | |
| | | | 200 | 0.94 | | | | | | | |
| | | | 225 | 1.04 | | | | | | | |

| 型号 代码 | D | M | L | 螺距 | H | S | V | V ₁ | 承载 (Kg) | 参考重量 (Kg/pcs) | | |
|----------|---------|-----|------|------|-----|----|----|----------------|------------|------------------|------|------|
| E-WAD81 | 100 | 16 | 75 | 2 | 24 | 10 | 13 | 800 | 1.23 | 1.25 | | |
| | | | 100 | | | | | | 1.27 | | | |
| | | | 125 | | | | | | 1.29 | | | |
| | | 150 | 1.31 | | | | | | | | | |
| | | 200 | 1.33 | | | | | | | | | |
| | | 250 | 1.35 | | | | | | | | | |
| | E-WAD82 | 20 | 150 | 150 | 2.5 | 26 | 30 | 13 | 900 | 1.32 | 1.35 | |
| | | | | 200 | | | | | | 1.38 | | |
| | | | | 250 | | | | | | 1.42 | | |
| | | | 300 | 1.46 | | | | | | | | |
| | | | 350 | 1.5 | | | | | | | | |
| | | | 400 | 1.54 | | | | | | | | |
| E-WAD83 | 24 | 100 | 100 | 3 | 36 | 16 | 19 | 950 | 1.93 | 1.98 | | |
| | | | 125 | | | | | | 2.03 | | | |
| | | | 150 | | | | | | 2.15 | | | |
| | | 200 | 2.2 | | | | | | | | | |
| | | 250 | 2.25 | | | | | | | | | |
| | | 300 | 2.3 | | | | | | | | | |
| | E-WAD84 | 20 | 150 | 150 | 2.5 | 30 | 13 | 16 | 1000 | 2.11 | 2.14 | |
| | | | | 200 | | | | | | 2.17 | | |
| | | | | 250 | | | | | | 2.22 | | |
| | | | 300 | 2.25 | | | | | | | | |
| | | | 350 | 2.28 | | | | | | | | |
| | | | 400 | 2.32 | | | | | | | | |
| E-WAD82 | 120 | 24 | 100 | 3 | 29 | 36 | 16 | 19 | 1050 | 2.14 | 2.2 | |
| | | | 125 | | | | | | | 2.2 | | |
| | | | 150 | | | | | | | 2.25 | | |
| | | 200 | 2.28 | | | | | | | | | |
| | | 250 | 2.32 | | | | | | | | | |
| | | 300 | 2.35 | | | | | | | | | |
| | E-WAD81 | 158 | 30 | 100 | 3.5 | 46 | 24 | 24 | 1200 | 2.45 | 2.48 | |
| | | | | 125 | | | | | | 2.52 | | |
| | | | | 150 | | | | | | 2.56 | | |
| | | | 200 | 2.63 | | | | | | | | |
| | | | 250 | 2.7 | | | | | | | | |
| | | | 300 | 2.78 | | | | | | | | |
| E-WAD83 | | 30 | 250 | 250 | 3.5 | 32 | 46 | 24 | 24 | 2000 | 5.44 | 5.63 |
| | | | | 300 | | | | | | | 5.87 | |
| | | | | 350 | | | | | | | 6.08 | |
| | | | 400 | 6.08 | | | | | | | | |

☑ 可选加工



| 型号 | D | M | L | 螺距 |
|---------|----|----|-----|------|
| E-WAD81 | 40 | 8 | 100 | 1.25 |
| E-WAD82 | 40 | 12 | 100 | 1.75 |

E-WAD81 — D60 — M16 — L100

| 型号 | D | M | L | 可选加工代码 |
|---------|----|----|-----|----------|
| E-WAD81 | 40 | 8 | 100 | WS WL BS |
| E-WAD82 | 40 | 12 | 100 | |

E-WAD81 — D60 — M16 — L100 — WS



| 数量 | 1~9 | 10~ |
|----|------|------|
| 价格 | 100% | 另行报价 |

| 交货期 |
|-----|
| 1 |

经济型防滑脚杯

可选加工



| 代码 | 技术说明 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|----|----------------------|---|----|----|----|----|----|---|----|---|----|----|----|----|----|----|------|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|--|--|
| WS | 螺杆末端加工外四角 | 选型方法 WS <table border="1"> <thead> <tr> <th>M</th> <th>n</th> <th>e</th> </tr> </thead> <tbody> <tr><td>10</td><td>6</td><td></td></tr> <tr><td>12</td><td>8</td><td>10</td></tr> <tr><td>14</td><td>10</td><td>12</td></tr> <tr><td>16</td><td>12</td><td>13.5</td></tr> <tr><td>20</td><td>14</td><td>15</td></tr> <tr><td>24</td><td>18</td><td>22</td></tr> </tbody> </table> | M | n | e | 10 | 6 | | 12 | 8 | 10 | 14 | 10 | 12 | 16 | 12 | 13.5 | 20 | 14 | 15 | 24 | 18 | 22 | | | | | | | | | | | |
| | | M | n | e | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 10 | 6 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 12 | 8 | 10 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 14 | 10 | 12 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 16 | 12 | 13.5 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 20 | 14 | 15 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 24 | 18 | 22 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| WL | 螺杆末端加工外六角 | 选型方法 WL <table border="1"> <thead> <tr> <th>M</th> <th>n1</th> <th>e1</th> </tr> </thead> <tbody> <tr><td>10</td><td>6</td><td></td></tr> <tr><td>12</td><td>8</td><td>10</td></tr> <tr><td>14</td><td>9</td><td></td></tr> <tr><td>16</td><td>10</td><td></td></tr> <tr><td>20</td><td>13</td><td>14</td></tr> <tr><td>24</td><td>16</td><td>18</td></tr> <tr><td>30</td><td>20</td><td>21</td></tr> </tbody> </table> | M | n1 | e1 | 10 | 6 | | 12 | 8 | 10 | 14 | 9 | | 16 | 10 | | 20 | 13 | 14 | 24 | 16 | 18 | 30 | 20 | 21 | | | | | | | | |
| | | M | n1 | e1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 10 | 6 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 12 | 8 | 10 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 14 | 9 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 16 | 10 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 20 | 13 | 14 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 24 | 16 | 18 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 30 | 20 | 21 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| BS | 螺杆末端加工扳手槽 | 选型方法 BS <table border="1"> <thead> <tr> <th>M</th> <th>n2</th> <th>ee</th> <th>e2</th> </tr> </thead> <tbody> <tr><td>10</td><td>8</td><td>8</td><td></td></tr> <tr><td>12</td><td>10</td><td></td><td></td></tr> <tr><td>14</td><td>12</td><td>10</td><td>12</td></tr> <tr><td>16</td><td>13</td><td></td><td></td></tr> <tr><td>20</td><td>17</td><td></td><td></td></tr> <tr><td>24</td><td>20</td><td>15</td><td>18</td></tr> <tr><td>30</td><td>26</td><td></td><td></td></tr> </tbody> </table> | M | n2 | ee | e2 | 10 | 8 | 8 | | 12 | 10 | | | 14 | 12 | 10 | 12 | 16 | 13 | | | 20 | 17 | | | 24 | 20 | 15 | 18 | 30 | 26 | | |
| | | M | n2 | ee | e2 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 10 | 8 | 8 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 12 | 10 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 14 | 12 | 10 | 12 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 16 | 13 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 20 | 17 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 24 | 20 | 15 | 18 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 30 | 26 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

| 代码 | 技术说明 | | | | | | | | | | | | | | | | | | | | | | |
|----|--------------------------------------|--|----|----|----|----|---|---|----|---|----|----|---|----|----|----|------|----|----|----|----|----|----|
| NS | 螺杆末端加工内四角 | 选型方法 NS <table border="1"> <thead> <tr> <th>M</th> <th>n3</th> <th>e3</th> </tr> </thead> <tbody> <tr><td>10</td><td>5</td><td></td></tr> <tr><td>12</td><td>6</td><td>10</td></tr> <tr><td>14</td><td>8</td><td>12</td></tr> <tr><td>16</td><td>10</td><td>13.5</td></tr> <tr><td>20</td><td>14</td><td>15</td></tr> <tr><td>24</td><td>18</td><td>20</td></tr> </tbody> </table> | M | n3 | e3 | 10 | 5 | | 12 | 6 | 10 | 14 | 8 | 12 | 16 | 10 | 13.5 | 20 | 14 | 15 | 24 | 18 | 20 |
| | | M | n3 | e3 | | | | | | | | | | | | | | | | | | | |
| 10 | 5 | | | | | | | | | | | | | | | | | | | | | | |
| 12 | 6 | 10 | | | | | | | | | | | | | | | | | | | | | |
| 14 | 8 | 12 | | | | | | | | | | | | | | | | | | | | | |
| 16 | 10 | 13.5 | | | | | | | | | | | | | | | | | | | | | |
| 20 | 14 | 15 | | | | | | | | | | | | | | | | | | | | | |
| 24 | 18 | 20 | | | | | | | | | | | | | | | | | | | | | |
| NL | 螺杆末端加工内六角 | 选型方法 NL <table border="1"> <thead> <tr> <th>M</th> <th>n4</th> <th>e4</th> </tr> </thead> <tbody> <tr><td>10</td><td>4</td><td>5</td></tr> <tr><td>12</td><td>6</td><td>8</td></tr> <tr><td>14</td><td>8</td><td>10</td></tr> <tr><td>16</td><td>10</td><td>12</td></tr> <tr><td>20</td><td>12</td><td>15</td></tr> <tr><td>24</td><td>16</td><td>18</td></tr> </tbody> </table> | M | n4 | e4 | 10 | 4 | 5 | 12 | 6 | 8 | 14 | 8 | 10 | 16 | 10 | 12 | 20 | 12 | 15 | 24 | 16 | 18 |
| | | M | n4 | e4 | | | | | | | | | | | | | | | | | | | |
| 10 | 4 | 5 | | | | | | | | | | | | | | | | | | | | | |
| 12 | 6 | 8 | | | | | | | | | | | | | | | | | | | | | |
| 14 | 8 | 10 | | | | | | | | | | | | | | | | | | | | | |
| 16 | 10 | 12 | | | | | | | | | | | | | | | | | | | | | |
| 20 | 12 | 15 | | | | | | | | | | | | | | | | | | | | | |
| 24 | 16 | 18 | | | | | | | | | | | | | | | | | | | | | |
| MS | 铆死底座与螺杆 铆死状态 正常状态 | 选型方法 MS ① 底座与螺杆铆死，可以提高底座和螺杆的连接刚度，但是底座与螺杆无法相对转动； ② 铆死后调节是底座也会随螺杆一起转动。 ③ 不适用于万向类型、橡胶底座型和非铆接组装的脚杯。 | | | | | | | | | | | | | | | | | | | | | |

- ① 请根据脚杯螺杆尺寸M进行加工参数的选择；
- ② 加工部不带镀层，有防锈漆；
- ③ 工具可根据不同加工类型进行选择，可选用开口扳手、活动扳手、内四角扳手、内六角扳手等。

脚杯

