


代码	类型		材质	使用温度
OBE01	全能型	直柱型	工程塑料	-40°C~+130°C
OBE02		肩型		


- 特点: 自润滑, 免维护, 耐脏污, 高性价比。
- 用途: 适用于中高负载、中等速度和中等温度。



直柱型
OBE01



肩型
OBE02



推荐配套轴公差: h9



直柱型

型号	代码	d	d公差	L		D	a	b					
OBE01	3	3	+0.054 +0.014	3	6	4.5							
	4	4		4	6	5.5							
	5	5	+0.068 +0.020	5	8	7		0.3					
	6	6		4	5	8							
	8	8		5	6	8							
	10	10	+0.083 +0.025	5	6	8	10	12	15	20	12		0.5
	12	12		6	8	10	12	15	20	25	14		
	14	14		8	10	15	20	25	16				
	15	15	+0.102 +0.032	10	12	15	20	25	17				
	16	16		10	12	15	20	25	18		0.5		
	18	18		10	12	15	20	25	20				0.8
	20	20		10	15	20	25	30	23				
	25	25	+0.124 +0.040	12	15	20	25	30	35	28			
	30	30		15	20	25	30	35	40	34			
	35	35		20	25	30	40	50	39				
40	40		20	30	40	50	44						
45	45	+0.150 +0.050	40	50	50							1.2	
50	50		20	25	30	40	50	55					

肩型

型号	代码	d	d公差	L		D	H	T	b					
OBE02	3	3	+0.054 +0.014	3	5	4.5	7.5	0.75						
	4	4		3	4	5.5	9.5							
	5	5	+0.068 +0.020	4	5	7	11		0.3					
	6	6		4	5	6	8	10						
	8	8		4	5.5	7.5	10	15						
	10	10	+0.083 +0.025	5	6	7	9	10	12	15	12	18		0.5
	12	12		5	6	7	9	10	12	15	17	20		
	14	14		8	10	12	15	17	21	16	22			
	15	15	+0.102 +0.032	9	12	17	20	17	23					
	16	16		9	12	17	21	18	24					
	18	18		9	12	17	22	30	20	26			0.8	
	20	20		11.5	16.5	21.5	23	30	23	30				
	25	25	+0.124 +0.040	11.5	16.5	21.5	30	28	35		1.5			
	30	30		16	20	26	37	45	34	42				
	35	35		12	16	26	36	39	47					
40	40		20	30	40	50	44	52						
45	45	+0.150 +0.050	30	50	50	58	50	58		2		1.2		
50	50		10	40	50	55	63							

直柱型

型号	代码	d	d公差	L
OBE01	3	3	+0.054 +0.014	3 6
	4	4	+0.068 +0.020	4 6

OBE01—d3—L6



优惠价
数量 1~9 10~
价格 100% 另行报价

未税价(元)

交货期
7



请按图示订货