

# 加厚 T 形导向轴支座

- 侧开口型
- 分离型




## 侧开口型

代码	类型	材质		表面处理	附件
		国标	相当		
GDC01	侧开口型	45	S45C	发黑	1个内六角圆柱头螺钉
GDC02					
GDC06		0Cr18Ni9	SUS304	喷细砂无电解镍	1个内六角圆柱头螺钉(不锈钢)
GDC08		LF2	A5052	喷细砂本色阳极氧化	



RoHS

- ① D30~40有2个附件内六角圆柱头螺钉。
- ① 开口型，安装孔D的公差H7为开口加工前的公差，开口加工后由于有内部应力释放，公差有可能增至H8左右，不影响客户使用。
- ① 如对防锈有要求，请优先选用不锈钢、铝合金材质或喷细砂无电解镍产品。



6.3



视角标准：第一视角

型号		H																											
代码	D <sub>H7</sub>	8	10	12	13	15	16	20	25	30	40	50	60	80	L	H <sub>1</sub>	T	T <sub>1</sub>	S	W	L <sub>1</sub>	d	E	M	d <sub>2</sub>	d <sub>1</sub>	h	N	
GDC01	8	10	15	20	25	30	40	50	60	62	H+10	15											11						
	10	12	13	15	20	25	30	40	50	60	H+11	18			5.8	37.8	50	6.6	12	M6深12	6.6	11	6.5					1.2~2.3	
	12	13	15	20	25	30	40	50	60	H+12	20																		
	13	15	20	25	30	40	50	60	H+14	20																			
	15	20	25	30	40	50	60	80	H+18	25			7.8	52.8	70	9	18												
	20	25	30	40	50	60	80	H+18	30																				
GDC02	25	30	40	50	60	80	H+21	35	17.5			61.8	82	6.6	22	M8深25	9	14	9										
	30	35	40	50	60	80	H+24	40	20			65.8	86	6.6	24														
	35	40	50	60	80	H+27	40	20			69.8	91	9	27															
	40																												

- ① 可能出现螺孔M底孔贯穿的情况。




## 分离型

代码	类型	材质		表面处理	附件
		国标	相当		
GDF01	分离型	45	S45C	发黑	2个内六角圆柱头螺钉
GDF02					
GDF06		0Cr18Ni9	SUS304	喷细砂无电解镍	2个内六角圆柱头螺钉(不锈钢)
GDF08		LF2	A5052	喷细砂本色阳极氧化	



RoHS

- ① D30~50有4个附件内六角圆柱头螺钉。
- ① 如对防锈有要求，请优先选用不锈钢、铝合金材质或喷细砂无电解镍产品。



6.3



视角标准：第一视角

型号		H																											
代码	D	8	10	12	13	15	16	20	25	30	40	50	60	80	L	H <sub>1</sub>	T	T <sub>1</sub>	S	W	L <sub>1</sub>	d	E	M	d <sub>2</sub>	d <sub>1</sub>	h	N	
GDF01	8	(10)	(15)	(20)	25	30	40	50	60	62	H+10	15											23						
	10	(10)	(15)	(20)	25	30	40	50	60	H+11	18																		
	12	(10)	(15)	(20)	25	30	40	50	60	H+12	18			5.8	37.8	50	6.6	24	M6深12	6.6	11	6.5							
	13	(15)	(20)	25	30	40	50	60	H+14	20																			
	15	(15)	(20)	25	30	40	50	60	H+18	25			7.8	52.8	70	9	36												
	20	(20)	25	30	40	50	60	80	H+18	30																			
GDF02	25	(20)	(25)	30	40	50	60	80	H+30	35	17.5			69.8	90	6.6	48	M8深16	9	14	9								
	30	(25)	30	40	50	60	80	H+30	40	20			75.8	96	9	56													
	35	(25)	30	40	50	60	80	H+40	50	25			101.8	128	11	76	M12深25	14	20	13									
	40	30	40	50	60	80	H+40	50	25																				
40																													

- ① 带( )的H尺寸对应的螺孔M底孔贯通。
- ① 可能出现螺孔M底孔贯通的情况。



分离型	
型号	D
GDF01	8
GDF02	10
GDF06	10
GDF08	10



优惠价	
数量	价格
1~9	100%
10~	另行报价



交货期
5