

常规型


| 代码    | 系列  | 类型     | 端子类型 |
|-------|-----|--------|------|
| ZID31 | Z系列 | 弹片式接线型 | 常规型  |

Weidmüller


CQC CE




规格: 252/252B




规格: 253/253B




规格: 2541/2541B




规格: 254/254B




规格: 255/255B



规格: 42/42B



规格: 62



视角标准: 第一视角


| 型号    |       | 导线最大<br>压接面积(mm²) | 通道数 | 层数  | 厚度  | 颜色  | 额定电压(V) |     |     |         | 额定电流(A) |    |     |         | 额定截面积(mm²) |             |     |         |
|-------|-------|-------------------|-----|-----|-----|-----|---------|-----|-----|---------|---------|----|-----|---------|------------|-------------|-----|---------|
| 代码    | 规格    |                   |     |     |     |     | IEC     | UL  | CSA | EN50019 | IEC     | UL | CSA | EN50019 | IEC        | UL          | CSA | EN50019 |
| ZID31 | 252   | 2.5               | 2   | 1   | 5.1 | 深灰色 | 800     | 600 | 600 | 550     | 24      | 25 | 27  | 21      | 2.5        |             | 2.5 |         |
|       | 252B  |                   |     |     |     | 蓝色  | 800     | 600 | 600 | 550     | 24      | 25 | 27  | 21      | 2.5        |             |     |         |
|       | 253   |                   | 3   |     |     | 深灰色 | 800     | 600 | 600 | 550     | 24      | 25 | 27  | 21      | 2.5        | AWG26~12    | 2.5 |         |
|       | 253B  |                   |     |     |     | 蓝色  | 800     | 600 | 600 | 550     | 24      | 25 | 27  | 21      | 2.5        |             |     |         |
|       | 2541  |                   |     |     |     | 深灰色 | 800     | 600 | 600 | 550     | 24      | 25 | 27  | 21      | 2.5        |             |     | 2.5     |
|       | 2541B |                   | 蓝色  |     |     | 800 | 600     | 600 | 550 | 24      | 25      | 27 | 21  | 2.5     |            |             |     |         |
|       | 254   | 4                 | 2   | 深灰色 |     | 500 | 300     | 300 | 275 | 20      | 10      | 10 | 18  | 2.5     | AWG26~14   | 2.5         |     |         |
|       | 254B  |                   |     | 蓝色  |     | 500 | 300     | 300 | 275 | 20      | 10      | 10 | 18  | 2.5     | AWG26~14   |             |     |         |
|       | 255   |                   |     | 深灰色 |     | 500 | 300     | 300 | 440 | 20      | 10      | 10 | 20  | 2.5     | AWG26~12   |             | 2.5 |         |
|       | 255B  |                   |     | 蓝色  |     | 500 | 300     | 300 | 440 | 20      | 10      | 10 | 20  | 2.5     | AWG26~12   |             |     |         |
| 42    | 4     | 2                 | 1   | 6.1 | 深灰色 | 800 | 600     | 600 | 550 | 32      | 33      | 35 | 28  | 4       | AWG26~10   | 4           |     |         |
| 42B   |       |                   |     |     | 蓝色  | 800 | 600     | 600 | 550 | 32      | 33      | 35 | 28  | 4       | AWG26~10   |             |     |         |
|       | 62    | 6                 | 2   | 1   | 8   | 深灰色 | 800     | 600 | 600 | 550     | 41      | 45 | 50  | 36      | 6          | 22~8   20~8 | 6   |         |

接地型


| 代码    | 系列  | 类型     | 端子类型 |
|-------|-----|--------|------|
| ZID47 | Z系列 | 弹片式接线型 | 接地型  |

Weidmüller

CQC CE




规格: 25




规格: 253




规格: 2541





规格: 254



规格: 40



规格: 62



视角标准: 第一视角

| 型号    |      | 导线最大<br>压接面积(mm²) | 通道数 | 层数  | 厚度  | 颜色 | 额定电压(V) |     |     |         | 额定短时<br>电流(A) | 额定截面积(mm²)               |                          |     |                             |     |
|-------|------|-------------------|-----|-----|-----|----|---------|-----|-----|---------|---------------|--------------------------|--------------------------|-----|-----------------------------|-----|
| 代码    | 规格   |                   |     |     |     |    | IEC     | UL  | CSA | EN50019 |               | IEC                      | UL                       | CSA | EN50019                     |     |
| ZID47 | 25   | 2.5               | 2   | 1   | 5.1 | 绿色 | 800     | 800 | 800 | 800     | 300           | 2.5                      | AWG26 ~ 12               |     |                             | 2.5 |
|       | 253  |                   | 3   |     |     |    | 800     | 800 | 800 | 550     | 300           |                          | AWG30 ~ 12    AWG26 ~ 12 |     |                             |     |
|       | 2541 |                   | 4   |     |     |    | 800     | 800 | 800 | 550     | 300           |                          | AWG26 ~ 14    AWG26 ~ 12 |     |                             |     |
|       | 254  | 4                 | 2   | 6.1 |     |    | 500     | 500 | 500 | 500     | —             | AWG26 ~ 14    AWG26 ~ 12 |                          |     |                             |     |
|       | 40   |                   | 2   |     |     |    | 1       | 6.1 | 800 | 800     | 800           | 800                      | 480                      | 4   | AWG26 ~ 10    4             |     |
|       | 62   |                   | 2   |     |     |    | 1       | 8.1 | 800 | 800     | 800           | 800                      | 480                      | 6   | AWG22 ~ 8    AWG20 ~ 8    6 |     |



请按图示订货

| 代码    | 型号 | 规格  | 导线最大<br>压接面积(mm <sup>2</sup> ) |
|-------|----|-----|--------------------------------|
| ZID47 | 25 | 254 | 2.5                            |

ZID47—25

接线端子