


高强度弓型卸扣

◀ X型/W型




代码	类型	材质	表面处理
TCD81	X型	碳钢	热镀锌
TCD83	W型	碳钢	热镀锌



X型
TCD81



W型
TCD83



视角标准：第一视角

■ X型

	型号	工作拉力 (T)	B ₁	B ₂	D	W	A	E	G	H	净重 (kg)
代码	规格										
TCD81	0.33T	0.33	4.8±0.5	4.8±0.5	6±0.2	9.7±1	21.6±2	15.3±1.5	14.2±1	37.5±2	0.025
	0.5T	0.5	6.4±0.5	6.4±0.5	7.5±0.2	12±1	28±2	19.8±1.5	15.5±1	46.8±2	0.042
	0.75T	0.75	9.7±0.8	8±0.8	9.5±0.2	13.5±1	29.8±2	21.4±1.5	19±1	53±2	0.008
	1T	1	9.7±0.8	9.7±0.8	11.2±0.2	16.8±1.2	35.5±2	26.2±2	23±1.5	63±2	0.146
	1.5T	1.5	11.2±0.8	11.2±0.8	13.4±0.3	19±1.2	42±2	29.5±2	27±1.5	74±2	0.225
	2T	2	13.5±0.8	13.6±0.8	15.2±0.3	20.6±1.2	47±2	33.3±2	30±1.5	84.2±2	0.338
	3.25T	3.25	16±1	17.6±1	19±0.3	27±1.2	59±3	43±2.5	38±2	106.5±3	0.71
	4.75T	4.75	19.5±1	20.6±1	21.2±0.3	32±1.5	71±3	50.8±2.5	46±2	126.5±3	1.187
	6.5T	6.5	22.4±1	24.6±1	25±0.3	36.6±1.5	83±3	58±2.5	53±2	148±3	1.829
	8.5T	8.5	25.4±1	27±1	28±0.3	43±1.5	94±3	68.4±2.5	60.5±2	166.6±3	2.693
	9.5T	9.5	29.5±1.5	31.8±1.5	30±0.5	46±1.5	108±4	74±3	68.3±3	190±4	3.915
	12T	12	32.7±2	35±1.5	36±0.5	51.6±2	117±4	82.5±3	76.2±3	209.6±4	5.661
	13.5T	13.5	36±2	36±1.5	39±0.5	57±2	134±4	92±3	84±3	232.7±4	6.84
	17T	17	39±2	41±1.5	48±0.5	60.5±2	146±4	99±3	92.2±3	254±4	8.78
	25T	25	46.7±2	57±2	56±0.5	73.2±3	177±4	127±4	106.4±3	313.5±4	17.818
35T	35	52.8±2.5	61±2	56±0.5	82.5±3	196±5	146±4	127±4	347.5±5	24.958	
55T	55	68.8±2.5	79.5±2	68±0.5	105±3	266±5	184±4	147.7±4	453±5	50.423	

① 破断拉力是工作拉力的6倍。

■ W型

	型号	工作拉力 (T)	B ₁ ±0.5	B ₂ ±0.5	D±0.2	W	A±2	E±1.2	G±1	H±2	净重 (kg)
代码	规格										
TCD83	0.33T	0.33	4.8	4.8	7.2	9.7 _{±1}	21.6	15.3	14.2	37.5	0.022
	0.5T	0.5	6.4	6.4	8.7	12 _{±1}	28	19.8	15.5	46.8	0.04
	0.75T	0.75	8	8	11	13.5 _{±1}	29.8	21.4	19	53	0.08
	1T	1	9.7	9.7	13.5	16.8 _{±1.2}	35.5	26.2	23	63.2	0.13
	1.5T	1.5	11.2	11.2	15	19 _{±1.2}	42	29.5	27	78	0.21
	2T	2	13.5	13.5	17.5	20.6 _{±1.2}	47	33.3	30	83.3	0.32
	3.25T	3.25	16	17.5	21.5	27 _{±1.2}	59	42.9	38	106.5	0.67
	4.75T	4.75	19	20.6	23.5	32 _{±1.5}	71	50.8	46	126.5	1.04
	6.5T	6.5	22.4	24.6	27.5	36.6 _{±1.5}	83	58	53	148	1.64
	8.5T	8.5	25.4	27	30.5	43 _{±1.5}	94	68.4	60.5	167	2.51
	9.5T	9.5	29.5	31.8	32.5	46 _{±1.5}	108	74	68.3	190	3.77
	12T	12	32.7	35	38.7	51.6 _{±2}	117	82.6	76.2	209.6	4.98
	13.5T	13.5	36	36	41.7	57 _{±2}	134	92.2	84	232.7	6.01
	17T	17	39	41	42	60.5 _{±2}	146	98.6	92.2	254	8.3
	25T	25	46.7	57	51	73.2 _{±3}	177	127	106.4	313.5	17
35T	35	52.8	61	59.5	82.5 _{±3}	196	146	127	347.5	21.7	
55T	55	68.8	79.5	70.5	105 _{±3}	266	184	147.7	453	45.6	

① 破断拉力是工作拉力的6倍。



请按图示订货

代码	规格
TCD81	0.33T
TCD81	0.5T

TCD81 — 0.33T



未税价(元)

数量	1~499	500~
价格	100%	另行报价



交货期
15