

加厚 T 形导向轴支座


标准型
开口型

标准型

代码	类型	材质		表面处理	附件
		国标	相当		
GCY01	标准型	45	S45C	发黑	1个紧定螺钉
GCY02				喷细砂无电解镀锌	1个紧定螺钉(不锈钢)
GCY06		0Cr18Ni9	SUS304	—	




来图定制




① D30~50有2个附件紧定螺钉。


② 如对防锈有要求，请优先选用不锈钢材质或喷细砂无电解镀锌产品。



D8~25



D30~50



视角标准：第一视角

型号		H							L	H ₁	T	T ₁	S	W	M	L ₁	d							
代码	D _{H7}																							
GCU01 GCU02 GCU06	8	+0.015 0	10	15	20	25	30	40	42	H+9	15	7.5	5.8	17.8	M6	30	6.6							
	10		10	15	20	25	30	40		50	60	H+10						18	9					
	12		10	15	20	25	30	40		50	60	H+11												
	13		15	20	25	30	40	50		60	H+12													
	15	+0.018 0	15	20	25	30	40	50	60	54	H+15	20	10	28.8		42								
	16		15	20	25	30	40	50	60		80	H+18	25					12.5						
	20		20	25	30	40	50	60	80		H+20	30	15					7.8	33.8		50	9		
	25		20	25	30	40	50	60	80		H+23	35	17.5										9.8	43.8
	30	+0.021 0	25	30	40	50	60	80	85	H+25	40	20												
	35		25	30	40	50	60	80		H+30														
	40		30	40	50	60	80	100		H+38								50	25	14.8	73.8			
	50		40	50	60	80	125			H+38								50	25					

开口型

代码	类型	材质		表面处理	附件
		国标	相当		
GCY01	开口型	45	S45C	发黑	1个内六角圆柱头螺钉
GCY02				喷细砂无电解镀锌	1个内六角圆柱头螺钉(不锈钢)
GCY06		0Cr18Ni9	SUS304	—	
GCY08		LF2	A5052	喷细砂本色阳极氧化	




来图定制




① D30~50有2个附件内六角圆柱头螺钉。

② 开口型，安装孔D的公差H7为开口加工前的公差，开口加工后由于有内部应力释放，公差有可能增至H8左右，不影响客户使用。


③ 如对防锈有要求，请优先选用不锈钢材质、铝合金材质或喷细砂无电解镀锌产品。



D8~25



D30~50



视角标准：第一视角

型号		H										L	H ₁	T	T ₁	S	W	L ₁	d	E	M	d ₂	d ₁	h	N			
代码	D _{H7}	8	10	15	20	25	30	40																				
GCY01 GCY02 GCY06 GCY08	+0.015 0	10	10	15	20	25	30	40	50	60	48	H+18	15	7.5	5.8	23.8	36	6.6	14	M6贯通	7	11	7	1.2~2.3				
		12	10	15	20	25	30	40	50	60		H+19																
		13	15	20	25	30	40	50	60	H+21																		
		15	15	20	25	30	40	50	60	H+23																		
	+0.018 0	16	15	20	25	30	40	50	60	80	67	H+29	25	12.5	7.8	34.8	50	9	19	M8贯通	9	14	9	1.2~3.5				
		20	20	25	30	40	50	60	80	H+31		30	15															
		25	25	30	40	50	60	80	H+33	35		17.5	9.8	44.8											65	6.6	27	M8深16
		35	25	30	40	50	60	80	H+36																			
	+0.021 0	40	30	40	50	60	80	100	H+38	40	20	125	H+51	50	25	14.8	74.8	100	11	29	M12深25	14	20	13				
		50	40	50	60	80																						

开口型

型号	代码	DH7	H
GCY01	8	+0.015	10 15 20 25
GCY02	10	0	10 15 20 25

请按图示订货 GCY02 — D8 — H10



未税价(元)

优惠价

数量	1~9	10~
价格	100%	另行报价



交货期

5