## 凸台型▶

## 树脂轴环










! 凸台作用于轴承内圈。





型号			L		-
代码	D	V	最小单位0.5	Н	Т
		3		5	
	8	4		6	
		3		5	
	10	4	2~40	7	,
		5	2~40	8	
		4	0	7	
	12	5	4.4	8	
		6		9	
		4		7	
	14	5	0.00	8	
	14	6	"	9	
		8		11	
		5	IV.	8	1.5
	15	6	5~50	9	1.5
聚甲醛	15	8	30~30	11	
UDF01		10		13	
		5	4	8	
MC尼龙	16	6	RT	9	
标准级	10	8 EX		11	
UDF06		10,0		13	
		M P 6		9	
	20	8 VITO 8		11	
	20	10		13	
		12	12 16		
		8		11	
	10 13				
	25	12	10~60	16 2	
		15	10 00	21	_
		16		22	
		10		13	
		12		16	
	30	15		21	
		16		22	
		20	0	25	

轴垫 环 圏

C1

		变更内径公差	增加径向紧固用螺孔	变更T尺寸	
丁选加工	可选加工		単螺孔 双螺孔 MB() L/2 MA() MB() MB()	TC()	
	代码	VC	MA()(单螺孔) MB()(双螺孔)	TC()	
	技术说明	选型方法  VC   V‡8計公差变更为V±81	透型方法 MB5	选型方法 TC3 ① 最小单位0.5	











