




代码	类型	材质	表面处理	
			国标	相当
ENS01	夹紧型	45	S45C	发黑
ENS11	梯形槽	铝合金		喷细砂本色阳极氧化

① 3D模型仅供参考，具体尺寸请以参数表为准，注意选型。



① M=M3时, $d_1=\varnothing 6.5$ $d_2=\varnothing 3.5$
M=M4时, $d_1=\varnothing 8$ $d_2=\varnothing 4.5$

视角标准：第一视角

型号	皮带半径	dH7选择	D	D1	D2	h	W	L	T	T1	V	X	Y	M	适用皮带直径
代码	A														
ENS01	20	4 5	16	22	18							5	3		
	30	1	20	32	28	1	2.2	11	5	2.5		7	3.5	M3	2
	40	4 5 6 6.35 8		42	38						2.5				
	30	4 5 6 6.35 8	20	32	27			16				7	3.5	M3	
	40	1.5		42	37	1.5	3.3								3
	45	4 5 6 6.35 8 10 11 12	25	47	42						4.5	9	4.5	M4	
	60			62	57			20							
	23			25	19										
	28			30	24										
	30	4 5 6 6.35 8	20	32	26			16			2.5	7	3.5	M3	
	40			42	36										4
	45	2		47	41	2	4.4								
	48	4 5 6 6.35 8 10 11 12	25	50	44						4.5	9	4.5	M4	
	60			62	56			20							
	80			82	76										
	28	4 5 6 6.35 8	20	30	23			16	10	5	2.5	7	3.5	M3	
	40			42	35										
	48			50	43										
	50	2.5	25	52	45	2.5	5.5	20			4.5	9	4.5	M4	5
	60	4 5 6 6.35 8 10 11 12		62	55										
ENS11	75			77	70										
	80			82	75										
	28	4 5 6 6.35 8	20	30	22			16			2.5	7	3.5	M3	
	38	4 5 6 6.35		40	32							6.5			
	48			50	42										
	50			52	44										
	58	3		60	52	3	6.6	20			4.5	9	4.5	M4	6
	60	4 5 6 6.35 8 10 11 12	25	62	54										
	75			77	69										
	95			97	89										
	100			102	94										

① 可选加工

型号	皮带半径	dH7选择
代码 A		
ENS01 20		4 5
ENS11 30		4 5 6 6.35 8

ENS01-A20-1-d5

型号	皮带半径	dH7选择	可选加工代码
代码 A			
ENS01 20		4 5	
ENS11 30		4 5 6 6.35 8	

ENS01-A20-1-d5-DC



数量	1~9	10~
价格	100% 另行报价	



数量	1~9	10~
价格	100% 另行报价	

请按图示订货

可选加工

代码	技术说明								
DC	切割D1尺寸 选型方法 DC ① 切割D1尺寸，减小外径； ② 外径切割的加工面可能不进行表面处理； ③ 适用皮带半径R1/R1.5/R2/R2.5以下规格； 适用皮带半径 DC <table> <tr> <td>1</td> <td>A+0.8</td> </tr> <tr> <td>1.5</td> <td>A+1.2</td> </tr> <tr> <td>2</td> <td>A+1.6</td> </tr> <tr> <td>2.5</td> <td>A+1.8</td> </tr> </table>	1	A+0.8	1.5	A+1.2	2	A+1.6	2.5	A+1.8
1	A+0.8								
1.5	A+1.2								
2	A+1.6								
2.5	A+1.8								