


日标

代码	类型	材质		硬度	表面处理	适用标准	
		国标	相当				
TBP11	E型	弹簧钢		42~51HRC	磷化黑	JIS B 2805-1978	
TBP13		0Cr18Ni9		SUS304	34~42HRC		—
TBP12		—		—	—		—

TBP11

TBP12



视角标准：第一视角

弹簧钢(磷化黑)/SUS304


代码	规格	d	D	H	t	d ₁ 的分类			d ₂			m	n (min)
						大于		以下	d ₂		m		
						1.4	2	1.23	0.4	0.6			
(弹簧钢)	1.2	1.2	3	±0.1	1	0.3	±0.025	1.4	2	1.23	0.4	0.6	
	1.5	1.5	4		1.3			2	2.5	1.53	0.5	0.8	
	2	2	5		1.7	0 -0.25	0.4	±0.03	2.5	3.2	2.05	0.5	0.8
	2.5	2.5	6		2.1			3.2	4	2.55	0.7	1	
	3	3	7		2.6			4	5	3.05	0.7	1	
(SUS304)	4	4	9	±0.2	3.5	0	0.6	±0.04	5	7	4.05	0.7	1.2
	5	5	11		4.3	0 -0.30	0.6	±0.04	6	8	5.05	0.9	1.2
	6	6	12		5.2		0.8	±0.04	7	9	6.05	0.9	1.8
	7	7	14		6.1	0 -0.35	0.8	±0.04	8	11	7.1	0.9	1.5
	8	8	16		6.9		0.8	±0.04	9	12	8.1	0.9	1.8
9	9	18		7.8		0.8	±0.04	10	13	9.1	0.9	2.1	

弹簧钢(镀黑锌)

代码	规格	d	D	H	t	d ₁ 的分类			d ₂			m	n (min)
						大于		以下	d ₂		m		
						1.4	2	1.23	0.4	0.6			
TBP13	1.2	1.2	3	±0.1	1	0.3	±0.025	1.4	2	1.23	0.4	0.6	
	1.5	1.5	4		1.3			2	2.5	1.53	0.5	0.8	
	2	2	5		1.7	0 -0.25	0.4	±0.03	2.5	3.2	2.05	0.5	0.8
	2.5	2.5	6		2.1			3.2	4	2.55	0.7	1	
	3	3	7		2.6			4	5	3.05	0.7	1	
4	4	9	±0.2	3.5	0	0.6	±0.04	5	7	4.05	0.7	1.2	
5	5	11		4.3	0 -0.30	0.6	±0.04	6	8	5.05	0.9	1.2	

国标

代码	类型	材质		表面处理	适用标准
		国标	相当		
TBP41	E型	65Mn(弹簧钢)		发黑	GB/T 896-1986
TBP42		0Cr18Ni9		SUS304	



TBP41

TBP42



视角标准：第一视角

代码	规格	d	H	t	D max	d ₂		m		n ≥	d ₁ >		
						基本尺寸	极限偏差	基本尺寸	极限偏差				
						0.9	±0.08	0.3	±0.03			3	1.2
(弹簧钢)	1.2*	1.2	3	±0.1	1	0.3	±0.025	1.4	2	1.23	0.4	0.6	
	1.5	1.5	4		1.3			2	2.5	1.53	0.5	0.8	
	2	2	5		1.7	0 -0.25	0.4	±0.03	2.5	3.2	2.05	0.5	0.8
	2.5	2.5	6		2.1			3.2	4	2.55	0.7	1	
	3	3	7		2.6			4	5	3.05	0.7	1	
(SUS304)	3.5*	3.5	9	±0.2	3.5	0	0.6	±0.04	5	7	4.05	0.7	1.2
	4	4	11		4.3	0 -0.30	0.6	±0.04	6	8	5.05	0.9	1.2
	5	5	12		5.2		0.8	±0.04	7	9	6.05	0.9	1.8
	6	6	14		6.1	0 -0.35	0.8	±0.04	8	11	7.1	0.9	1.5
	8	8	16		6.9		0.8	±0.04	9	12	8.1	0.9	1.8
9	9	18		7.8		0.8	±0.04	10	13	9.1	0.9	2.1	

带*号规格不适用TBP42。

国标

代码	规格	公称直径 d
TBP41	1.5	1.5
TBP42	2	2

TBP41—1.5



● 优惠价
数量 1~45 46~
价格 100% 另行报价



交货期
7

请按图示订货

未税价(元)