


螺纹圆形连接器

弯角型插头 经济型

代码	类型		连接方式	材质			表面处理	
				外壳	绝缘体	接触体	外壳	接触体
ZIX47	经济型	弯角型插头	螺纹连接	锌合金	热塑塑料PPS (耐高温260°C)	铜	镀铬	镀金



代码	型号 外壳形状	规格	芯数	端头	D	H	L	d(max)	额定电流 (A)	工作电压 (V)	耐压 (V)	接触电阻 (MΩ)	绝缘电阻 (MΩ)	适配插座代码											
ZIX47	TS (弯式双压板 电缆插头)	20	2	J(插针)	31	56	60	13.5	10	AC500	AC1500	2.5	2000	ZIX56 ZIX57 ZIX58 ZIX59											
															3	5	6	7	9	12	10	5	5	5	5
															4	6	7	9	12	10	5	5	5	5	5
															5	6	7	9	12	10	5	5	5	5	5
															6	7	9	12	10	5	5	5	5	5	5
															7	9	12	10	5	5	5	5	5	5	5
															9	12	10	5	5	5	5	5	5	5	5
															12	10	5	5	5	5	5	5	5	5	5
															10	5	5	5	5	5	5	5	5	5	5
															12	5	5	5	5	5	5	5	5	5	5
															10	5	5	5	5	5	5	5	5	5	5
															12	5	5	5	5	5	5	5	5	5	5
															16	5	5	5	5	5	5	5	5	5	5
															17	5	5	5	5	5	5	5	5	5	5
															20	5	5	5	5	5	5	5	5	5	5
															24	5	5	5	5	5	5	5	5	5	5
26	5	5	5	5	5	5	5	5	5	5															

❗ 插针头必须和插孔头配合使用。



型号			
代码	外壳形状	规格	芯数 端头
ZIX47	TS	20	2 J(插针) 3 K(插孔)

请按图示订货 ZIX47-TS-20-2-J

📊 性能表

连接方式	螺纹连接
接线方式	焊接
接插次数	500次
温度范围	-40°C~+85°C

