


代码	类型	材质	使用温度
OBE01	直柱型	尼龙66(PA66)	-40°C~+130°C
OBE02	肩型	含润滑剂与特殊填充剂	


- 特点: 自润滑, 免维护, 耐脏污, 高性价比。
 用途: 适用于中高负载、中等速度和中等温度。



直柱型
OBE01



肩型
OBE02



推荐配套轴公差: h9



直柱型

代码	型号	d公差	L	D	a	b
OBE01	3	+0.054 +0.014	3 6	4.5	0.3	0.3
	4		4 6	5.5		
	5	+0.068 +0.020	5 8 10	7		
	6		4 5 6 8 10	8		
	8	+0.083 +0.025	5 6 8 10 12 15	10		
	10		5 6 8 10 12 15 20	12		
	12		6 8 10 12 15 20 25	14	0.5	0.5
	14		8 10 15 20 25	16		
	15	+0.102 +0.032	10 12 15 20 25	17		
	16		10 12 15 20 25	18		
	18		10 12 15 20 25	20		
	20		10 15 20 25 30	23		
	25	+0.124 +0.040	12 15 20 25 30 35	28	1.2	1.2
	30		15 20 25 30 35 40	34		
	35		20 25 30 40 50	39		
	40	+0.150 +0.050	20 30 40 50	44		
	45		40 50	50		
	50		20 25 30 40 50	55		

肩型

型号		d公差	L	D	H	T	b
代码	d						
OBE02	3	+0.054 +0.014	3 5	4.5	7.5	0.75	0.3
	4		3 4 6	5.5	9.5		
	5	+0.068 +0.020	4 5 10	7	11		
	6		4 5 6 8 10	8	12		
	8	+0.083 +0.025	4 5.5 7.5 10 15	10	15		
	10		5 6 7 9 10 12 15	12	18		0.5
	12		5 6 7 9 10 12 15 17 20	14	20	1	
	14		8 10 12 15 17 21	16	22		
	15	+0.102 +0.032	9 12 17 20	17	23		
	16		9 12 17 21	18	24		
	18		9 12 17 22 30	20	26		0.8
	20		11.5 16.5 21.5 30	23	30	1.5	
	25	+0.124 +0.040	11.5 16.5 21.5 30	28	35		
	30		16 20 26 37 45	34	42		
	35		12 16 26 36	39	47		
40		20 30 40 50	44	52	2	1.2	
45	+0.150 +0.050	30 50	50	58			
50		10 40 50	55	63			

直柱型

代码	型号	d公差	L
OBE01	3	+0.054 +0.014	3 6
	4	+0.068 +0.020	4 6

OBE01—d3—L6

优惠价

数量	1~9	10~
价格	100%	另行报价

未税价(元)

交货期
7

