


吊钩

羊角滑沟/羊角安全钩


代码	类型		材质	表面处理
TCD41	G80羊角滑沟	带舌片型	合金钢	喷漆(红色)
TCD42	G80羊角安全钩	自锁型		
TCE41	G100羊角滑沟	带舌片型		喷漆(蓝色)
TCE42	G100羊角安全钩	自锁型		




G80羊角滑沟
TCD41




G80羊角安全钩
TCD42



G100羊角滑沟
TCE41



G100羊角安全钩
TCE42



视角标准：第一视角

G80羊角滑沟

代码	规格	工作拉力 (T)	A \pm 0.5	B \pm 1.5	L \pm 1	H \pm 2	E \pm 2	净重 (kg)
TCD41	1.12T	1.12	8	32	109	23	26	0.32
	3.15T	3.15	12.5	49	161.5	31	39	0.95
	5.3T	5.3	16.5	56.5	203	42.5	47.5	1.8
	8T	8	21.5	70.5	248	54	56	3.4
	12.5T	12.5	24	77	297	58	59	6
	15T	15	26	91	326	62	72	10.4

① 破断拉力是工作拉力的4倍。

G80羊角安全钩

代码	规格	工作拉力 (T)	A	B	L	K	E	P	H	T	净重 (kg)
TCD42	1.12T	1.12	8 \pm 0.5	32 \pm 1	134 \pm 3	99 \pm 3	32 \pm 2	28 \pm 1	73 \pm 2	15 \pm 0.5	0.44
	2T	2	9.5 \pm 0.5	38.5 \pm 1	162 \pm 3	119 \pm 3	40 \pm 3	35 \pm 1	91 \pm 2	20 \pm 0.5	0.8
	3.15T	3.15	12.5 \pm 0.5	46 \pm 1	195 \pm 3	142 \pm 3	48 \pm 3	45 \pm 2	108 \pm 2	26 \pm 1	1.38
	5.3T	5.3	15 \pm 0.5	59 \pm 1	248 \pm 4	179 \pm 4	57 \pm 3	52.5 \pm 2	142 \pm 3	33 \pm 1	2.81
	8T	8	18.5 \pm 0.5	77 \pm 1.5	310 \pm 4	225 \pm 4	65 \pm 4	63 \pm 2	168.6 \pm 3	38 \pm 2	6
	12.5T	12.5	24 \pm 1	81 \pm 1.5	335 \pm 5	238 \pm 5	82 \pm 4	82 \pm 2	185 \pm 4	50 \pm 2	7.25
	15T	15	25 \pm 1	97.5 \pm 2	392 \pm 5	277 \pm 5	80 \pm 5	76 \pm 3	202 \pm 4	52 \pm 2	12.8
	21.2T	21.2	30 \pm 1.5	118 \pm 2	449 \pm 6	312 \pm 6	109 \pm 5	96 \pm 4	239 \pm 5	60 \pm 3	21.8
	31.5T	31.5	35 \pm 1.5	150 \pm 2	590 \pm 6	416 \pm 6	131 \pm 6	131 \pm 4	329 \pm 5	79.5 \pm 3	49.6

① 破断拉力是工作拉力的4倍。

G100羊角安全钩

代码	规格	工作拉力 (T)	A	B	L	K	E	P	H	T	净重 (kg)
TCE42	1.4T	1.4	8 \pm 0.5	32 \pm 1.5	131 \pm 4	96 \pm 4	31.5 \pm 2	28 \pm 2	73 \pm 2	15 \pm 1	0.5
	2.5T	2.5	9.5 \pm 0.5	36 \pm 1.5	163 \pm 4	121 \pm 4	40 \pm 3	36 \pm 3	90 \pm 2	20 \pm 1	0.9
	4T	4	12 \pm 0.5	46 \pm 1.5	194 \pm 5	144 \pm 5	46 \pm 3	45 \pm 3	108 \pm 3	26 \pm 1.5	1.4
	6.7T	6.7	15 \pm 1	59 \pm 1.5	251 \pm 5	182 \pm 5	66 \pm 4	53.6 \pm 3	137 \pm 3	32.5 \pm 1.5	2.9
	10T	10	18.5 \pm 1	70 \pm 2	303 \pm 6	220 \pm 6	75 \pm 4	61 \pm 4	168 \pm 3	38 \pm 2	5.5
	12.5T	12.5	22 \pm 1	78 \pm 2	322 \pm 6	227 \pm 6	76 \pm 5	73 \pm 4	183 \pm 3	44 \pm 2	8.5
	16T	16	25 \pm 1.5	85 \pm 2	337 \pm 7	235 \pm 7	80 \pm 5	76.5 \pm 4	190 \pm 3	50 \pm 3	8.6
	19T	19	25.5 \pm 2	98 \pm 2.5	386 \pm 8	271 \pm 8	104 \pm 5	76 \pm 4	202 \pm 4	52 \pm 3	12.1
	26.5T	26.5	30 \pm 2	118 \pm 2.5	484 \pm 8	343 \pm 8	107 \pm 5	99 \pm 4	251 \pm 4	60 \pm 3	21.15

① 破断拉力是工作拉力的4倍。

G100羊角滑沟

代码	规格	工作拉力 (T)	A \pm 0.5	B \pm 1	L \pm 2.5	H \pm 1	E \pm 1.5	净重 (kg)
TCE41	1.4T	1.4	7.5	32	109	21	18.5	0.33
	2.5T	2.5	9.5	37	134	27.5	25	0.7
	4T	4	12	46	161.5	33.5	28	1.3
	6.7T	6.7	15	59	203	42	38	2.3
	10T	10	18.5	70	248	50	44	3.6
	16T	16	25	85	297	56	52	7
	19T	19	27	100	326	62	66	12.1

① 破断拉力是工作拉力的4倍。

请按照图示订货

型号
代码 规格
TCD41 1.12T

优惠价

数量 1~9 10~
价格 100% 另行报价

未税价(元)

交货期

15