



弯接头 外螺纹

精密型 耐热快速接头

代码	类型		材质			表面处理
			主体	螺纹部	密封部材料	主体
J-XYP31	外螺纹	弯接头	黄铜	黄铜	耐热NBR	镀镍



视角标准：第一视角

型号		公称 型号	R	D	A	B	L	P	C ₁	C ₂	E	S	喷嘴直径	有效断面面积 (mm ²)	重量(g)
代码	d														
J-XYP31	4	M5	M5		3	19	20.8								
		1	R1/8	6	8	22	22.8	9.7	17.6	15	20.5	10	1.8	1.5	15
		2	R1/4		11	25	23.8					14	2.5	3.5	17
															22
	6	M5	M5		3	20.7	23.6						1.8	1.9	23
		1	R1/8		8	23.7	25.6					12			25
		2	R1/4	8	11	26.7	26.6	11.8	19.4	16	23.3	14	4	9	29
		3	R3/8		12	28.5	28.1					17			39
	8	1	R1/8		8	25	27.9								32
		2	R1/4	10	11	28	28.8	13.7	20.2	17	24.8	14	6	16	35
		3	R3/8		12	29.8	30.3								44
	10	1	R1/8		8	27.5	32.3					17		22.5	55
		2	R1/4	12	11	30.5	33.2	17.5	23.2	23	29.3				58
		3	R3/8		12	31.5	33.9							30	58
		4	R1/2		15	34.5	35.1					21	8		80
	12	2	R1/4		11	31	35.4							38	87
		3	R3/8	14	12	32	36.1	20.8	26.3	19.5	33.4	21	9	39	92
		4	R1/2		15	35	37.2								103



型号		公称 型号	R
代码	d		
J-XYP31	4	M5	M5
	1	R1/8	R1/8
J-XYP31-d4-M5			



优惠价	数量	1~29	30~
价格	100%	另行报价	



气动
调节阀类
D8