

滚子轴承随动器

双轨道双列滚子型 经济型

代码	类型			材质	
	经济型	全滚子带内圈型	圆柱型 球面型	国标	相当
E-BPQ21			圆柱型	GCr15	SUJ2
E-BPQ26			球面型		


◎ 圆柱型D公差:

D	公差
35~47	$0_{-0.011}^0$
52~80	$0_{-0.013}^0$
90~110	$0_{-0.015}^0$


◎ 球面型D公差: $0_{-0.05}^0$



圆柱型
E-BPQ21



球面型
E-BPQ26



Ⓜ 不承诺品牌。

视角标准: 第一视角

代码	型号		dr	D	B	B ₁	r (min)	r ₁ (min)	基本额定负荷(KN)		最大静态容许 负荷(KN)	极限转速 (rpm)	重量 (g)
	d	d							Cr(动)	Cor(静)			
圆柱型 E-BPQ21	15		20	35	18	19	0.6	0.3	10.08	11.68	7.55	4800	99
	15A	$0_{-0.008}^0$		42					11.76	12.96	12.96		158
	17			40					11.44	14.32	12.99		147
	17A		22	47	20	21			12.72	14.72	14.72	4000	220
	20			47					19.6	24.4	17.41		245
	20A		31	52	24	25	1	0.5	21.6	28	28	4800	321
	25	$0_{-0.010}^0$		52					20	26.4	19.2		281
	25A			62					24	34	34		450
	30		38	62	28	29			28	36.4	22.53	1760	465
	30A			72					32.8	44.8	44.8		697
球面型 E-BPQ26	35		44	72	30	32			30.8	43.2	36.48	1440	630
	35A			80					34.8	50.4	50.4		836
	40		49	80	30	32			36	48.8	48.19	1200	816
	40A			90					41.6	60	60		1129
	45	$0_{-0.012}^0$	53	85	30	32	1.1	0.6	36.8	52.8	50.37	1040	883
	45A			100					44.8	68	68		1396
	50			90					36.8	52.8	52.54		950
	50A		58	110	30	32			47.2	75.2	75.2	880	1690

Ⓜ 上表中极限转速数值仅适用润滑脂型号, 若采用油润滑的型号极限转速为上述数值的160%左右。



请按图示订货

型号	
代码	d
E-BPQ21	15A
E-BPQ21	d15

E-BPQ21 - d15



未税价(元)

优惠价	
数量	价格
1~49	100% 另行报价
50~	



交货期
5