




代码	类型	材质	最大压缩量
YSWG	特重载荷型 标准型	油冷回火弹簧钢	L×20%

L尺寸公差

L	公差
50以下	±0.5
50以上	±1.0%

- ① 载荷(±10%)
- ① 直角度(2°以下)
- ① 载荷(N)=定数(N/mm)×压缩量
- ① 耐热温度为150℃
- ① 1kgf=9.81N
- ① 压紧长度为参考值, 加工时会略有差异。
- ① 弹簧颜色和圈数可能会因生产批次不同而异, 但产品性能均符合标准, 不影响使用!



视角标准: 第一视角

型号	内径	弹簧常数	a	使用方法							
				30万次F=L×20%	50万次F=L×18%	100万次F=L×16%					
代码	D	L	d	压紧长度	Fmm	负载N	Fmm	负载N	Fmm	负载N	
YSWG	10	15	5	163.3	11.4	容许范围以外	2.7		2.4		
		20		122.5	15.0	4	3.6		3.2		
		25		98.0	19.0	5	4.5		4		
		30		81.7	22.8	6	5.4		4.8		
		35		70.0	26.6	7	6.3		5.6		
		40		61.3	30.4	8	7.2		6.4		
		45		54.4	34.2	9	8.1		7.2		
		50		49.0	38.0	10	9	441.3	8	392	
		55		44.5	41.8	11	9.9		8.8		
		60		40.8	45.6	12	10.8		9.6		
	12	65		37.7	49.4	13	11.7		10.4		
		70		35.0	53.2	14	12.6		11.2		
		75		32.7	57.0	15	13.5		12		
		80		30.6	60.8	16	14.4		12.8		
		90		27.2	68.4	18	16.2		14.4		
		100		24.5	76.0	20	18		16		
		15	6	245.0	11.4	容许范围以外	2.7		2.4		
		20		183.8	15.0	4	3.6		3.2		
		25		147.0	19.0	5	4.5		4		
		30		122.5	22.8	6	5.4		4.8		
		35		105.0	26.6	7	6.3		5.6		
		40		91.9	30.4	8	7.2		6.4		
		45		81.7	34.2	9	8.1		7.2		
		50		73.5	38.0	10	9	662	8	588	
		55		66.8	41.8	11	9.9		8.8		
		60		61.3	45.6	12	10.8		9.6		
YSWG	14	65	7	56.5	49.4	13	11.7		10.4		
		70		52.5	53.2	14	12.6		11.2		
		75		49.0	57.0	15	13.5		12		
		80		45.9	60.8	16	14.4		12.8		
		90		40.8	68.4	18	16.2		14.4		
		100		36.8	76.0	20	18		16		
		20	8	237.8	15.2	容许范围以外	3.6		3.2		
		25		190.3	19.0	5	4.5		4		
		30		158.5	22.8	6	5.4		4.8		
		35		135.9	26.6	7	6.3		5.6		
		40		118.9	30.4	8	7.2		6.4		
		45		105.7	34.2	9	8.1		7.2		
		50		95.1	38.0	10	9		8		
		55		86.5	41.8	11	9.9	856	8.8	761	
		60		79.3	45.6	12	10.8		9.6		
		65		73.2	49.4	13	11.7		10.4		
YSWG	16	70		67.9	53.2	14	12.6		11.2		
		75		63.4	57.0	15	13.5		12		
		80		59.5	60.8	16	14.4		12.8		
		90		52.8	68.4	18	16.2		14.4		
		100		47.6	76.0	20	18		16		
		20		318.8	15.2	容许范围以外	3.6		3.2		
		25		255.0	19.0	5	4.5		4		
		30		212.5	22.8	6	5.4		4.8		
YSWG		35		182.1	26.6	7	6.3		5.6		
		40		159.4	30.4	8	7.2		6.4		
		45		141.7	34.2	9	8.1		7.2		

型号	内径	弹簧常数	a	使用方法							
				30万次F=L×20%	50万次F=L×18%	100万次F=L×16%					
代码	D	L	d	压紧长度	Fmm	负载N	Fmm	负载N	Fmm	负载N	
YSWG	16	50	8	127.5	38.0	10		9	8		
		55		115.9	41.8	11		9.9	8.8		
		60		106.3	45.6	12		10.8	9.6		
		65		98.1	49.4	13	1275	11.7	10.4	1020	
		70		91.1	53.2	14		12.6	11.2		
		75		85.0	57.0	15		13.5	12		
		80		79.7	60.8	16		14.4	12.8		
		90		70.8	68.4	18		16.2	14.4		
		100		63.8	76.0	20		18	16		
	18	20	9	392.2	15.2	容许范围以外		3.6	3.2		
		25		313.8	19.0	5		4.5	4		
		30		261.5	22.8	6		5.4	4.8		
		35		224.1	26.6	7		6.3	5.6		
		40		196.1	30.4	8		7.2	6.4		
		45		174.3	34.2	9		8.1	7.2		
		50		156.9	38.0	10		9	8		
		55		142.6	41.8	11	1569	9.9	1412	8.8 1255	
		60		130.7	45.6	12		10.8	9.6		
		65		120.7	49.4	13		11.7	10.4		
YSWG	20	70	10	112.1	53.2	14		12.6	11.2		
		75		104.6	57.0	15		13.5	12		
		80		98.0	60.8	16		14.4	12.8		
		90		87.2	68.4	18		16.2	14.4		
		100		78.4	76.0	20		18	16		
	22	20	11	515	15.2	容许范围以外		3.6	3.2		
		25		412	19	5		4.5	4		
		30		343	22.8	6		5.4	4.8		
		35		294	26.6	7		6.3	5.6		
		40		257	30.4	8		7.2	6.4		
		45		229	34.2	9		8.1	7.2		
		50		206	38	10		9	8		
		55		187	41.8	11	2059	9.9	1853	8.8 1648	
		60		172	45.6	12		10.8	9.6		
		65		158	49.4	13		11.7	10.4		
YSWG		70		147	53.2	14		12.6	11.2		
		75		137	57	15		13.5	12		

矩形弹簧

特重载荷弹簧(黑色)

型号		内径	弹簧	a	使用方法			
代码	D	L	d	压簧长度	Fmm	负载N	Fmm	负载N
		80	11	147	60.8	16	14.4	12.8
		90		131	68.4	18	16.2	14.4
		100		118	76	20	18	16
		125		94.1	95	25	22.5	20
		20		760	15.2	容许范围以外	3.6	3.2
		25		608	19	5	4.5	4
		30		507	22.8	6	5.4	4.8
		35		434	26.6	7	6.3	5.6
		40		380	30.4	8	7.2	6.4
		45		338	34.2	9	8.1	7.2
		50		304	38	10	9	8
		55		276	41.8	11	9.9	8.8
		60		253	45.6	12	10.8	9.6
		65		234	49.4	13	11.7	10.4
		70		217	53.2	14	12.6	11.2
		75		203	57	15	13.5	12
		80		190	60.8	16	14.4	12.8
		90		169	68.4	18	16.2	14.4
		100		152	76	20	18	16
		125		122	95	25	22.5	20
		20		907.2	15.2	容许范围以外	3.6	3.2
		25		726	19	5	4.5	4
		30		605	22.8	6	5.4	4.8
		35		518	26.6	7	6.3	5.6
		40		454	30.4	8	7.2	6.4
		45		403	34.2	9	8.1	7.2
		50		363	38	10	9	8
		55		330	41.8	11	9.9	8.8
		60		302	45.6	12	10.8	9.6
		65		279	49.4	13	11.7	10.4
		70		259	53.2	14	12.6	11.2
		75		242	57	15	13.5	12
		80		227	60.8	16	14.4	12.8
		90		202	68.4	18	16.2	14.4
		100		181	76	20	18	16
		125		145	95	25	22.5	20
		150		121	114	30	27	24
		20		1176.9	15.2	容许范围以外	3.6	3.2
		25		941	19	5	4.5	4
		30		785	22.8	6	5.4	4.8
		35		672	26.6	7	6.3	5.6
		40		588	30.4	8	7.2	6.4
		45		523	34.2	9	8.1	7.2
		50		471	38	10	9	8
		55		428	41.8	11	9.9	8.8
		60		392	45.6	12	10.8	9.6
		65		362	49.4	13	11.7	10.4
		70		336	53.2	14	12.6	11.2
		75		314	57	15	13.5	12
		80		294	60.8	16	14.4	12.8
		90		262	68.4	18	16.2	14.4
		100		235	76	20	18	16
		125		188	95	25	22.5	20
		150		157	114	30	27	24
		175		134	133	35	31.5	28
		200		118	152	40	36	32
		30		1029.8	22.8	6	5.4	4.8
		35		882.7	26.6	7	6.3	5.6
		40		772	30.4	8	7.2	6.4
		45		686	34.2	9	8.1	7.2
		50		618	38	10	9	8
		55		562	41.8	11	9.9	8.8
		60		515	45.6	12	10.8	9.6
		65		475	49.4	13	11.7	10.4
		70		441	53.2	14	12.6	11.2
		75		412	57	15	13.5	12
		80		386	60.8	16	14.4	12.8
		90		343	68.4	18	16.2	14.4
		100		309	76	20	18	16
		125		247	95	25	22.5	20

型号		内径	弹簧	a	使用方法			
代码	D	L	d	压簧长度	Fmm	负载N	Fmm	负载N
		150	15	206	114	30	27	24
		175		177	133	35	31.5	28
		200		154	152	40	36	32
		35		1148.8	26.6	7	6.3	5.6
		40		1005	30.4	8	7.2	6.4
		45		893	34.2	9	8.1	7.2
		50		804	38	10	9	8
		55		731	41.8	11	9.9	8.8
		60		670	45.6	12	10.8	9.6
		65		619	49.4	13	11.7	10.4
		70		574	53.2	14	12.6	11.2
		75		536	57	15	13.5	12
		80		503	60.8	16	14.4	12.8
		90		447	68.4	18	16.2	14.4
		100		402	76	20	18	16
		125		322	95	25	22.5	20
		150		268	114	30	27	24
		175		230	133	35	31.5	28
		200		201	152	40	36	32
		50		1226	39	10	9	8
		55		1114	43	11	9.9	8.8
		60		1022	47	12	10.8	9.6
		65		943	51	13	11.7	10.4
		70		876	54	14	12.6	11.2
		75		817	58	15	13.5	12
		80		766	61	16	14.4	12.8
		90		681	66	18	16.2	14.4
		100		613	74	20	18	16
		125		490	89	25	22.5	20
		150		409	105	30	27	24
		175		350	133	35	31.5	28
		200		306	152	40	36	32
		60		1117	45.6	12	10.8	9.6
		70		957	53.2	14	12.6	11.2
		80		670	76	20	18	16
		150		447	114	30	27	24



请按图示订货

型号	内径
代码 D L	d
YSWG	10

YSWG - D20 - L20



未税价(元)

优惠价
数量 1~99 100~
价格 100% 另行报价



交货期
10