


调心滚子轴承

圆锥孔型 进口型

代码	类型		油槽/油孔	轴承类型 代码	轴承精度	后置代码	轴承材质	
	进口型	圆锥孔型					国标	相当
J-BBZ02	进口型	圆锥孔型	有	2	GB/T 307.1 0级	E(钢保持架, 内圈无挡边, 优化的内部设计, 用于提高承载能力) K(圆锥孔型, 锥度1:12)	GCr15	SUJ2



安装孔



视角标准: 第一视角

型号	d	D	B	b	k	r (min)	额定载荷		极限转速(r/min)		安装尺寸			重量 (Kg) (参考)
							Cr(动) KN	Cor(静) KN	脂润滑	油润滑	da (min)	Da (max)	Fa (max)	
J-BBZ02-22205EK	25	52	18				36.5	36	8500	11000	31	46		0.18
J-BBZ02-22206EK	30	62	20	3.7	2	1	49	49	7500	9500	36	56	1	0.28
J-BBZ02-22207EK	35	72	23			1.1	69.5	71	6500	8500	42	65		0.44
J-BBZ02-22208EK		80					79	88.5	6000	7600	47	73		0.52
J-BBZ02-22308EK	40	90	33	6		1.5	121	128	4500	5900	48.5	81.5	1.5	0.95
J-BBZ02-22209EK		85	23	5.5		1.1	82.5	95	5300	6800	52	78	1	0.57
J-BBZ02-21309EK	45	25	25				102	106	4400	5700				0.91
J-BBZ02-22309EK		100	36	6		1.5	148	167	4100	5300	53.5	91.5	1.5	1.3
J-BBZ02-22210EK		90	23	5.5		1.1	86	102	4900	6300	57	83	1	0.62
J-BBZ02-21310EK	50	27	27		3		118	127	4000	5200				1.19
J-BBZ02-22310EK		110	40	6		2	186	212	3700	4800	60	100	2	1.75
J-BBZ02-22211EK		100	25			1.5	118	144	4400	5800	63.5	91.5	1.5	0.79
J-BBZ02-21311EK	55	29	29				145	163	3700	4800				1.69
J-BBZ02-22311EK		120	43	5.5		2	204	234	3400	4400	65	110	2	2.25
J-BBZ02-22212EK		110	28			1.5	150	182	4000	5300	68.5	101.5	1.5	1.07
J-BBZ02-21312EK	60	31	31				167	191	3400	4400				2.07
J-BBZ02-22312EK		130	46	8.3	4.5	2.1	238	273	3100	4000	72	118	2	2.83
J-BBZ02-21313EK	65	33	33	6	3		194	228	3100	4000				2.51
J-BBZ02-22313EK		140	48	8.3	4.5		265	320	2800	3700	77	128	2	3.37
J-BBZ02-22214EK		125	31			1.5	184	232	3400	4600	78.5	116.5	1.5	1.47
J-BBZ02-21314EK	70	35	35		3		220	262	2900	3800				3.14
J-BBZ02-22314EK		150	51	8.3	4.5	2.1	325	380	2700	3500	82	138	2	4.12
J-BBZ02-22215EK		130	31			1.5	190	246	3200	4200	83.5	121.5	1.5	1.55
J-BBZ02-21315EK	75	37	37		3		239	287	2700	3500				3.76
J-BBZ02-22315EK		160	55	8.3	4.5	2.1	330	410	2500	3200	87	148		5.13
J-BBZ02-22216EK		140	33			2	213	277	3000	4000	90	130		1.94
J-BBZ02-21316EK	80	39	39	6	3		260	315	2500	3300				4.47
J-BBZ02-22316EK		170	58	8.3	4.5	2.1	385	470	2300	3000	92	158		5.91
J-BBZ02-22217EK		150	36			2	251	320	2800	3800	95	140		2.43
J-BBZ02-21317EK	85	41	41		3		289	355	2400	3100				5.28
J-BBZ02-22317EK		180	60	8.3	4.5		415	510	2200	2900	99	166	2.5	6.94
J-BBZ02-21318EK	90	43	43	8.3	4.5	3	320	400	2300	3000				6.21
J-BBZ02-22318EK		190	64	11.1	6		480	590	2100	2700	104	176	2.5	8.16
J-BBZ02-22219EK		170	43	8.3	4.5	2.1	294	390	2500	3300	107	158	2	4.01
J-BBZ02-22319EK	95	200	67	11.1	6	3	500	615	1900	2500	109	186	2.5	9.54
J-BBZ02-22220EK		180	46			2.1	315	415	2400	3200	112	168	2	4.84
J-BBZ02-21320EK	100	47	47	8.3	4.5		370	465	2000	2600				8.78
J-BBZ02-22320EK		215	73	11.1	6	3	605	755	1800	2400	114	201	2.5	12.1
J-BBZ02-22222EK		200	53	8.3	4.5	2.1	410	570	2200	2800	122	188	2	7.04
J-BBZ02-22322EK	110	240	80	13.9	7.5	3	745	930	1700	2200	124	226	2.5	16.7
J-BBZ02-22224EK	120	215	58			2.1	485	700	2000	2600	132	203	2	8.89
J-BBZ02-22226EK	130	230	64	11.1	6		570	790	1800	2400	144	216		10.9
J-BBZ02-22228EK	140	250	68	6	3	3	685	975	1700	2200	154	236	2.5	13.7
J-BBZ02-22230EK	150	270	73	13.9	7.5		775	1160	1600	2000	164	256		17.7
J-BBZ02-22236EK	180	320	86	16.7	9	4	1040	1610	1300	1700	198	302	3	28.6

关节轴承

E7



请按图示订货

型号	d	D
J-BBZ02-22205EK	25	52
J-BBZ02-22206EK	30	62
J-BBZ02-22207EK	35	72

J-BBZ02-22206EK



未税价(元)

数量	1~9	10~
价格	100%	另行报价



交货期

6

1Kg=9.81N