

内六角圆柱头螺钉



全牙 / 半牙 · 粗牙 / 细牙
标准型

代码	类型	螺纹	材质		强度等级	
			国标	相当		
TAC21	标准型	全牙/半牙	粗牙	0Cr18Ni9	SUS304	A2-70
TAC05		全牙	细牙	0Cr17Ni12Mo2	SUS316	A4-70
TAC09			粗牙	—	黄铜	—
TAD01			粗牙	—	—	—
TAD02		粗牙	—	—	—	

全牙



半牙



视角标准：第一视角

适用标准：DIN 912-1983、GB/T 70.1-2000

常规型

型号	L															V	P 螺距	D	K	S																			
代码	M																																						
TAC21	1.6	3	4	5	6	8	10	12	14	16						全牙	0.35	3	1.6	1.5																			
	2	3	4	5	6	8	10	12	14	16	18	20	22	25	30		35	40	0.4		3.8	2																	
	2.5	3	4	5	6	8	10	12	14	16	18	20	22	25	30					0.45	4.5	2.5	2																
	3	5				6	8	10	12	14	16	18	20	22	25		30	35	40	0.5	5.5	3	2.5																
	4	5				6	8	10	12	14	16	18	20	22	25					20	0.7	7	4	3															
	5	6						8	10	12	14	16	18	20	22	25	30	35	40	45	50	55	60	全牙	22	0.8	8.5	5	4										
	6	8						10	12	14	16	18	20	22	25	30				30	35	40	45		50	55	60	65	70	80									
	8	35				40	45	50	55	60	65	70	75	80	85	90	100	110	120	130				全牙	24	1.0	10	6	5										
	10	10						12	14	16	18	20	22	25	30	35	40	45	50	55	60	65	70	75	80	90	95	100	110	120	130	140	150	全牙	28	1.25	13	8	6
	12	16						18	20				25	30	35				100	110	120	130	140	150															
	14	45						50	55	60	65	70	75	80	85	90	100	110	120	130	140	150				全牙	32	1.5	16	10	8								
	16	20						25	30	35	40	45	50				100	110	120	130	140	150				全牙	36	1.75	18	12	10								
	20	55						60	65	70	75	80	85	90	100	110	120	130	140	150				全牙	40	2.0	21	14	12										
20	20						25	30	35	40	45	50	55				100				全牙	44	2.0	24	16	14													
20	60						65	70	80	90	100				100	110	120	130	140	150				全牙	52	2.5	30	20	17										

加长型

型号		L														V	P 螺距	D	K	S	
代码	M																				
TAC05	3	30 35 40 45 50 55 60															0.5	5.5	3	2.5	
	4	30 35 40 45 50 55 60 65 70 75 80 100 110 120															0.7	7	4	3	
	5	30 35 40 45 50 55 60 65 70 75 80 85															0.8	8.5	5	4	
	6	30 35 40 45 50 55 60 65 70 75 80 85 90 100 110 120 130 140 150															1.0	10	6	5	
	8	20 25	40 45 50 55 60 65 70 75 80 85 90 95 100 110 120 130 140 150 160														全牙	1.25	13	8	6
			45 50 55 60 65 70 75 80 85 90 100 110 120 130 140 150															1.5	16	10	8
	12		55 60 65 70 75 80 85 90 100 110 120 130 140 150															1.75	18	12	10
	16		65 70 75 80 90 100 110 120 130 140 150															2.0	24	16	14
	20		80 90 100 110 120 130 140 150															2.5	30	20	17

SUS304 · 细牙

型号		L													V	P 螺距	D	K	S
代码	M																		
TAC09	6	10	12	16	20	25	30	35	40	45	50			全牙	0.75	10	6	5	
	8	16	20	25	30	35	40	45	50	60	70	80	90		100	1.0	13	8	6
	10	20	25	30	35	40	45	50	60	70	80	90	100		1.0	16	10	8	
	12	20	25	30	35	40	45	50	60	70	80	90	100		1.5	18	12	10	

SUS316

型号		L														V	P 螺距	D	K	S					
代码	M																								
TAD01	2.5	4	6	8	10	12											0.45	4.68	2.5	2					
	3		5	6	8	10	12	16		20	25	30					0.5	5.5	3	2.5					
	4			6	8	10	12	14	16	18	20	25	30	35			0.7	7	4	3					
	5				8	10	12		16	18	20	25	30	35	40	45	50	0.8	8.5	5	4				
	6					8	10	12	14	16		20	25	30	35	40	45	50	55	60	70	80			
	8						12	14	16			20	25	30	35	40	45	50	55	60	65	80			
	10							16			20	25	30	35	40	45	50	55	60	65	70	75	80	90	100
	12										20	25	30	35	40	45	50	55	60	65	70	75	80	90	100
	14											25	30	35	40	45	50		60						
	16												25	30	35	40	45	50	55	60	70		80	90	100
	20												40	45	50	55	60	65	70		80	90	100		

黄铜

型号		L										V	P 螺距	D	K	S
代码	M															
TAD02	6	10	12	16	20	25	30					1	10	6	5	
	8				20	25	30	35	40		50	1.25	13	8	6	
	10				20	25	30	35	40		50	1.5	16	10	8	
	12							30	35	40	45	50	60	1.75	18	12

常规型

型号		L			
代码	M				
TAC21	3	5	6	8	10
	4	5	6	8	10
	5	8 10			

请按图示订货

TAC21—M3—L6

优惠价

数量	1~49	50~
价格	100% 另行报价	



未税价(元)



交货期
3

螺丝·螺母·垫圈·吊环

C2