



| 代码    | 类型 | 螺纹 | 强度等级  | 材质       |        | 表面处理 |
|-------|----|----|-------|----------|--------|------|
|       |    |    |       | 国标       | 相当     |      |
| TAH66 | 全牙 | 细牙 | 8.8   | 35K      |        | 发黑   |
| TAH67 |    |    | 10.9  | ML40Cr   |        |      |
| TAH05 |    |    | 12.9  |          |        |      |
| TAH06 |    |    | A2-70 | 0Cr18Ni9 | SUS304 |      |

TAH05

TAH06



TAH66/67 适用标准: GB/T 5786-2016  
 TAH05/06 适用标准: GB/T 5786-2000



35K

| 代码    | M   | L                          | P<br>螺距 | S   |       | K      |        |
|-------|-----|----------------------------|---------|-----|-------|--------|--------|
|       |     |                            |         | max | min   | max    | min    |
| TAH66 | 8   | 16 20 25 30 40             | 1       | 13  | 12.73 | 5.45   | 5.15   |
|       | 10  | 16 20 25 30 35 40 45 50    | 1.25    | 16  | 15.73 | 6.58   | 6.22   |
|       | 12  | 20 25 30 35 40 45 50       |         | 18  | 17.73 | 7.68   | 7.32   |
|       | 12A | 25 30 35 40 45 50          | 1.5     | 21  | 20.67 | 8.98   | 8.62   |
|       | 14  | 25 30 35 40 50             |         | 24  | 23.67 | 10.18  | 9.82   |
|       | 16  | 30 35 40 45 50 55 65 70 80 |         | 30  | 29.67 | 12.715 | 12.285 |
|       | 20  | 40 45 50 65                |         |     |       |        |        |

ML40Cr(强度等级: 10.9)

| 代码    | M   | L  | P<br>螺距 | S   |       | K      |        |
|-------|-----|--|---------|-----|-------|--------|--------|
|       |     |  |         | max | min   | max    | min    |
| TAH67 | 10  | 40   | 1       | 16  | 15.73 | 6.58   | 6.22   |
|       | 10A | 25   | 1.25    | 18  | 17.73 | 7.68   | 7.32   |
|       | 12  | 30 35 40 45 50   |         | 21  | 20.67 | 8.98   | 8.62   |
|       | 14  | 30 35 40 45 55   | 1.5     | 24  | 23.67 | 10.18  | 9.82   |
|       | 16  | 30 35 40 45 50 55                                      |         | 27  | 26.67 | 11.715 | 11.285 |
|       | 18  | 35 40 45 50 60   |         | 30  | 29.67 | 12.715 | 12.285 |
|       | 20  | 40 50 55 65  | 2       | 41  | 40    | 17.35  | 16.65  |
|       | 27  | 50 60 70 80 90 100 120 150                             |         | 46  | 45    | 19.12  | 18.28  |
|       | 30  | 50 60 70 80 90 100 110 120 130 140 150 160 180 200 240 |         | 50  | 49    | 21.42  | 20.58  |
|       | 33  | 80 90 100 120  |         | 55  | 53.8  | 22.92  | 22.08  |
|       | 36  | 60 65 70 80 90 95 100 110 120 130 140 150 160 180 200  | 3       | 60  | 58.8  | 25.42  | 24.58  |
|       | 39  | 80 90 100 110 120 130 140 150                          |         | 65  | 63.1  | 26.42  | 25.58  |
|       | 42  | 70 80 90 110 120 130 140 150 160 180 200 220 240 260   |         |     |       |        |        |

ML40Cr(强度等级: 12.9)

| 代码    | M                          | L                             | P<br>螺距 | S     |        | K      |        |
|-------|----------------------------|-------------------------------|---------|-------|--------|--------|--------|
|       |                            |                               |         | max   | min    | max    | min    |
| TAH05 | 8                          | 16 20 25 30 35 40 45 50       | 1       | 13    | 12.73  | 5.45   | 5.15   |
|       | 10                         | 20 25 30 35 40 45 50          |         | 16    | 15.73  | 6.58   | 6.22   |
|       | 12                         | 25 30 35 40 45 50 55 60       | 1.5     | 18    | 17.73  | 7.68   | 7.32   |
|       | 14                         | 30 35 40 45 50 55 60          |         | 21    | 20.67  | 8.98   | 8.62   |
|       | 16                         | 35 40 45 50 55 60 65 70       |         | 24    | 23.67  | 10.18  | 9.82   |
|       | 18                         | 35 40 45 50 55 60 65 70 80    | 2       | 27    | 26.67  | 11.715 | 11.285 |
|       | 20                         | 30 35 40 45 50 55 60 65 70 80 |         | 30    | 29.67  | 12.715 | 12.285 |
|       | 22                         | 45 50 55 60 65 70 80          |         | 34    | 33.38  | 14.215 | 13.785 |
| 24    | 40 45 50 55 60 65 70 80 90 |                               | 36      | 35.38 | 15.215 | 14.785 |        |

SUS304

| 代码    | M  | L                       | P<br>螺距 | S     |        | K      |      |
|-------|----|-------------------------|---------|-------|--------|--------|------|
|       |    |                         |         | max   | min    | max    | min  |
| TAH06 | 8  | 16 20 25 30 35 40 45 50 | 1       | 13    | 12.73  | 5.45   | 5.15 |
|       | 10 | 25 30 45 50             |         | 16    | 15.73  | 6.58   | 6.22 |
|       | 12 | 25 30 35 40 45 60       | 1.5     | 18    | 17.73  | 7.68   | 7.32 |
|       | 14 | 35 40 50 60             |         | 21    | 20.67  | 8.98   | 8.62 |
|       | 16 | 35 40 50                |         | 24    | 23.67  | 10.18  | 9.82 |
| 20    | 80 |                         | 30      | 29.67 | 12.715 | 12.285 |      |

SUS304

| 代码    | M  | L                 |
|-------|----|-------------------|
| TAH05 | 10 | 20 25 30 35 40 45 |
|       | 12 | 25 30 35 40 45    |

TAH06—M10—L25



| 优惠价 |           |
|-----|-----------|
| 数量  | 1-45 46~  |
| 价格  | 100% 另行报价 |

| 交货期 |   |
|-----|---|
| 数量  | 7 |