## ○帯螺栓孔型


l	代码	类型	材	表面处理	
			国标	相当	表固处理
l	UAS01				_
l	UAS02		45	S45C	发黑
l	UAS03	带螺栓孔型			无电解镀镍
l	UAS07		0Cr18Ni9	SUS304	
l	UAS08		LY11	A2017	本色阳极氧化








如对防锈有要求,请优先选用不锈钢材质或无电解镀镍产品。










型号		V	Q	Т	d	适用
代码	D	最小单位0.1	最小单位0.1	最小单位0.5	u	螺钉
	20	2.0~6.0	10.0~13.0		3.3	M3
	25	2.0~10.0	10.0~17.0			
UAS01 UAS02	30	2.0~10.0	12.0~20.0			
UAS03	35	2.0~16.0	12.0~25.0	1.0~12.0	4.3	M4
UAS07 UAS08	40	2.0~20.0	12.0~30.0			
	50	2.0~22.0	14.0~35.0		F 2	145
	60	2.0~28.0	14.0~40.0		5.3	M5









◯ 可选加工

型号		W	0	T 3	可洗加丁代码		
代码	D		Q	1 39	312311		
UASD1	20	2.0~6.0	10.0~13.0	10000	RCD)		
UAS02	25	2.(~10.0	10. ~ 7.0	1.000	CO		
UAS01-D25-V10-Q17-T10-FC3							







## ◎ 形状选择型

代码	类型	材	表面处理	
1 (1)=3	天空	国标	相当	衣田处理
UAU01				1 - 10
UAU02	形状选择型	45	S45C	发黑
UAU03	加州起井里			无电解镀镍
UAU07		0Cr18Ni9	SUS304	_











! 如对防锈有要求,请优先选用不锈钢材质或无电解镀镍产品。


形状选择: A

形状选择:B


形状选择: C


形状选择: D


形状选择: E





视角标准:第一 视角












型号		D	V	X	Т
代码	形状选择	最小单位0.5	最小单位0.5	最小单位0.1	最小单位0.1
UAU01 UAU02 UAU03 UAU07	ABCDE	10.0~20.0	3.0~40.0	<b>3.0~48.0</b> (A形不选择)	3.0~12.0











请按图示订货

UAU01—B—D15—V3—X5—T5

轴垫 环 圈 C1