


# 脚杯

## 固定调节型 超重载型 梯形螺纹

代码	类型	螺纹规格	材质		表面处理
			底座	螺杆	
WAD12	固定调节型	梯形螺纹	S45C	S45C	镀锌
WAD13			SUS304	SUS304	镀铬
WAD14			SUS304	SUS304	—

- 特点
  - 梯形螺纹的设计，使脚杯与设备之间的接触面积变大，可分散设备负载并提高承载能力。
  - 由于市面上钢材位为5mm一个梯度，且存在公差，因此车制底座公差-2~0mm均为合理范围。
  - 标准螺杆长度以25mm为个梯度，可根据客户要求定制长度，需要注意定制长度后，切断的面无表面处理，碳钢会喷漆防锈。



型号		Tr	L	螺距	S	S <sub>1</sub>	H	V	V <sub>1</sub>	垂直承载 (Kg)	参考重量 (Kg/pcs)
代码	D										
WAD12 WAD13 WAD14	80	16	50	4	24	22	26	10	19	2500	0.86
			75								0.90
			100								0.93
		125	0.96								
		150	1.02								
		75	1.05								
	80	20	100	4	30	29	26	13	19	3000	1.08
			125								1.14
			150								1.19
		200	1.30								
		100	1.29								
		125	1.32								
	80	24	125	4	36	35	26	16	24	4000	1.37
			150								1.45
			200								1.61
		50	1.25								
		75	1.29								
		100	1.32								
	100	16	125	4	24	22	26	10	19	3500	1.35
			150								1.41
			200								1.46
		250	1.52								
		300	1.59								
		75	1.44								
100	20	100	4	30	29	26	13	19	4500	1.47	
		125								1.53	
		150								1.58	
	200	1.69									
	250	1.80									
	300	1.91									
100	24	100	4	36	35	26	16	24	5500	1.68	
		125								1.76	
		150								1.84	
	200	2.00									
	250	2.16									
	300	2.32									
120	20	100	4	30	29	26	13	19	5500	1.94	
		125								2.00	
		150								2.05	
	200	2.16									
	250	2.27									
	300	2.38									
120	24	100	4	36	35	26	16	24	6000	2.15	
		125								2.23	
		150								2.31	
	200	2.47									
	250	2.63									
	300	2.79									
120	30	100	6	46	44	26	24	30	6500	2.64	
		125								2.76	
		150								2.88	
	200	3.12									
	250	3.36									
	300	3.60									



型号		Tr	L
代码	D		
WAD12	D80	16	50
WAD13	D80	20	75



优惠价	
数量	1~19 20~
价格	100% 另行报价

交货期	
数量	10

WAD12—D80—Tr16—L50