



代码	类型	材质	使用温度
OBE01	直柱型	尼龙66(PA66)	-40℃~+130℃
OBE02	肩型	含润滑剂与特殊填充剂	


特点: 自润滑, 免维护, 耐脏污, 高性价比。

用途: 适用于中高负载、中等速度和中等温度。


该产品为压配式衬套, 内径公差为压入座孔H7后公差, 压入后采用通止规进行测量(自由状态下请勿用卡尺进行测量)。

安装时保证H7座孔表面光滑、平整, 安装端倒角25°。禁止直接击打端面, 避免产品变形影响尺寸。


直柱型
OBE01



肩型
OBE02



推荐配套轴公差: h9



直柱型

型号	代码	d	d公差	L	D	a	b
OBE01	3	+0.054 +0.014	3 6	4.5			
	4		4 6	5.5			
	5	+0.068 +0.020	5 8 10	7			0.3
	6		4 5 6 8 10	8			
	8	+0.083 +0.025	5 6 8 10 12 15	10			
	10		5 6 8 10 12 15 20	12			0.5
	12		6 8 10 12 15 20 25	14			
	14		8 10 15 20 25	16			
	15	+0.102 +0.032	10 12 15 20 25	17		0.5	
	16		10 12 15 20 25	18			
	18		10 12 15 20 25	20			0.8
	20		10 15 20 25 30	23			
	25	+0.124 +0.040	12 15 20 25 30 35	28			
	30		15 20 25 30 35 40	34			
	35		20 25 30 40 50	39			
	40	+0.150 +0.050	20 30 40 50	44			1.2
	45		40 50	50			
	50		20 25 30 40 50	55			

肩型

型号	代码	d	d公差	L	D	H	T	b
OBE02	3	+0.054 +0.014	3 5	4.5	7.5	0.75		
	4		3 4 6	5.5	9.5			0.3
	5	+0.068 +0.020	4 5 10	7	11			
	6		4 5 6 8 10	8	12			
	8	+0.083 +0.025	4 5.5 7.5 10 15	10	15			
	10		5 6 7 9 10 12 15	12	18			0.5
	12		5 6 7 9 10 12 15 17 20	14	20	1		
	14		8 10 12 15 17 21	16	22			
	15	+0.102 +0.032	9 12 17 20	17	23			
	16		9 12 17 21	18	24			
	18		9 12 17 22 30	20	26			0.8
	20		11.5 16.5 21.5	23	30	1.5		
	25	+0.124 +0.040	11.5 16.5 21.5 30	28	35			
	30		16 20 26 37 45	34	42			
	35		12 16 26 36	39	47			
	40	+0.150 +0.050	20 30 40 50	44	52	2		1.2
	45		30 50	50	58			
	50		10 40 50	55	63			

直柱型

型号	代码	d	d公差	L
OBE01	3	+0.054 +0.014	3 6	
	4	+0.068 +0.020	4 6	

OBE01—d3—L6



未税价(元)

优惠价

数量	1~9	10~
价格	100%	另行报价



交货期

7



请按图示订货