

标准型·细牙
左旋螺纹·粗牙/细牙

六角螺母

标准型

代码	类型	螺纹	材质		表面处理	适用标准	强度等级
			国标	相当			
TBK58	标准型	细牙	45	S45C	发黑	GB/T 6171-2000	—
TBK59					镀锌		
TBK65			0Cr18Ni9	SUS304	发黑		
TBK60			10B21		发黑		



TBK58/60



TBK59



TBK65



视角标准：第一视角

型号		螺距 P	m		S		e
代码	M		(max)	(min)	(max)	(min)	(min)
(S45C) TBK58	8	1	6.8	6.44	13	12.73	14.38
	10		8.4	8.04	16	15.73	17.77
	12		10.8	10.37	18	17.73	20.03
	14	1.5	12.8	12.1	21	20.67	23.36
	16		14.8	14.1	24	23.67	26.75
	18		15.8	15.1	27	26.16	29.56
	20		18	16.9	30	29.16	32.95
	22	2	19.4	18.1	34	33	37.29
	24		21.5	20.2	36	35	39.55
	10		8.4	8.04	16	15.73	17.77
(S45C) TBK59	12	1.25	10.8	10.37	18	17.73	20.03
	14	1.5	12.8	12.1	21	20.67	23.36
	16		14.8	14.1	24	23.67	26.75
	18		15.8	15.1	27	26.16	29.56
	20	1.5	18	16.9	30	29.16	32.95
(SUS304) TBK65	8	1	6.8	6.44	13	12.73	14.38
	10		8.4	8.04	16	15.73	17.77
	12		10.8	10.37	18	17.73	20.03
	14	1.25	12.8	12.1	21	20.67	23.36
	16		14.8	14.1	24	23.67	26.75
	18		15.8	15.1	27	26.16	29.56
	20	1.5	18	16.9	30	29.16	32.95
	22		19.4	18.1	34	33	37.29
	24		21.5	20.2	36	35	39.55
	27	1.5	23.8	22.5	41	40	45.2



请按图示订货

型号	
代码	M
TBK58	8
TBK59	10

TBK58—M8



未税价(元)


优惠价	
数量	1~4 5~
价格	100% 另行报价



交货期	
数量	7

左旋螺纹

代码	类型	螺纹	材质		表面处理
			国标	相当	
TBK25	左旋 螺纹	粗牙	碳钢		镀锌
TBK26					发黑
TBK27		细牙	0Cr18Ni9	SUS304	—
TBK28					



视角标准：第一视角

型号		螺距 P	m		S		e
代码	M		(max)	(min)	(max)	(min)	(min)
粗牙 TBK25 TBK26 TBK27	4	0.7	3.2	2.9	7	6.78	7.66
	5	0.8	4	3.7	8	7.78	8.79
	6	1	5	4.7	10	9.78	11.05
	8*	1.25	6.5	6.14	13	12.73	14.38
	10*	1.5	8	7.64	17	16.73	18.9
	12*	1.75	10	9.64	19	18.67	21.1
	16*	2	13	12.3	24	23.67	26.75
	18*	2.5	15	14.3	27	26.16	29.56
	20*	2.5	16	14.9	30	29.16	32.95
	24*	3	19	17.7	36	35	39.55
细牙 TBK28	16*	1.5	13	12.3	24	23.67	26.75
	18*	2	15	14.3	27	26.16	29.56
	20*	2.5	16	14.9	30	29.16	32.95
	24*	3	19	17.7	36	35	39.55



请按图示订货

型号	
代码	M
TBK25	4
TBK26	5

TBK25—M4



未税价(元)

优惠价	
数量	1~49 50~
价格	100% 另行报价



交货期	
数量	7

TBK25/26/28仅适用带*号规格。