

# O型圈平面密封过渡接头

## 公制螺纹

直接头/90°弯接头/T型三通接头




### 直接头

代码	类型	材质
WSB01	外螺纹	碳钢
WSB02	外螺纹	SUS304

规格: 14/18/22/30/36

规格: 14A/16A/18A/22A/30A

规格: 14B/16B/22B/30B





视角标准: 第一视角

型号		M	N	A	B	L	S
WSB01 WSB02	14	M14×1.5	M14×1.5	11	11	28	17
	14A		M12×1.5				
	14B		M16×1.5				
	16A	M16×1.5	M14×1.5	11	11	28	19
	16B		M18×1.5				
	18	M18×1.5	M18×1.5	11	28	19	22
	18A		M16×1.5				
					11.5	31.5	22

型号		M	N	A	B	L	S
WSB01 WSB02	22	M22×1.5	M22×1.5	12	12.5	34.5	24
	22A		M18×1.5				
	22B		M18×1.5				
	30	M30×1.5	M30×1.5	14	18.5	43.5	32
	30A		M27×2				
	30B	M36×2	M18×1.5	16	16	45.5	38
	36		M36×2				

### 90°弯接头-外螺纹



代码	类型	材质
WSB06	外螺纹	碳钢
WSB07	外螺纹	SUS304



视角标准: 第一视角

### 90°弯接头-内外螺纹

代码	类型	材质
WSB08	内外螺纹	碳钢
WSB09	内外螺纹	SUS304





视角标准: 第一视角

型号		M	A	S
WSB06 WSB07	14	M14×1.5	22.5	14
	18	M18×1.5	26	19
	22	M22×1.5	29	22
	30	M30×1.5	35.5	30
	36	M36×2	42	36

型号		M	A	B	S	S <sub>1</sub>
WSB08 WSB09	14	M14×1.5	22.5	8.5	19	14
	18	M18×1.5	26	8.5	24	19
	22	M22×1.5	29	10	27	22
	30	M30×1.5	35.5	11	36	30
	36	M36×2	42	13	41	36

### T型三通接头

代码	类型	材质
WSB11	外螺纹	碳钢
WSB12	外螺纹	SUS304



视角标准: 第一视角

型号		M	A	S
WSB11 WSB12	14	M14×1.5	22.5	14
	18	M18×1.5	26	19
	22	M22×1.5	29	22
	30	M30×1.5	35.5	30
	36	M36×2	42	36

### T型三通接头

型号			M
代码	规格		
WSB11	14	M14×1.5	
WSB12	18	M18×1.5	

请按图示订货

WSB11-14

未税价(元)	● 优惠价	数量	1~19	20~
	价格	100%	另行报价	

交货期	7
-----	---

液  
压  
接  
头

K2