

侧开口型
分离型

加厚 T 形导向轴支座

侧开口型




代码	类型	材质		表面处理	附件
		国标	相当		
GDC01	侧开口型	45	S45C	发黑	1个内六角圆柱头螺钉
GDC02		0Cr18Ni9	SUS304	喷细砂无电解镍	1个内六角圆柱头螺钉(不锈钢)
GDC06		LF2	A5052	喷细砂本色阳极氧化	



来图定制



- ① D30~40有2个附件内六角圆柱头螺钉。
② 开口型，安装孔D的公差H7为开口加工前的公差，开口加工后由于有内部应力释放，公差有可能增至H8左右，不影响客户使用。
③ 如对防锈有要求，请优先选用不锈钢材质、铝合金材质或喷细砂无电解镍产品。



视角标准：第一视角

型号		H							L	H ₁	T	T ₁	S	W	L ₁	d	E	M	d ₂	d ₁	h	N		
代码	D _{H7}																							
GDC01 GDC02 GDC06 GDC08	8	+0,015 0	10	15	20	25	30	40		H+10 H+11	15	7.5					11							
	10		10	15	20	25	30	40	50	60														
	12		10	15	20	25	30	40	50	60	62	H+12	18	9	5.8	37.8	50	6.6	12	M6深12	6.6	11	6.5	1.2~2.3
	13	+0,018 0		15	20	25	30	40	50	60														
	15		15	20	25	30	40	50	60		H+14	20	10											
	16		15	20	25	30	40	50	60															
	20			20	25	30	40	50	60	80	85	H+18	25	12.5	7.8	52.8	70	9	18					
	25	+0,021 0		20	25	30	40	50	60	80		30	15											
	30			25	30	40	50	60	80	102	H+21	35	17.5		61.8	82	6.6	22	M8深25	9	14	9	1.2~3.5	
	35	+0,025 0		25	30	40	50	60	80	106	H+24			9.8	65.8	86		24						
40							40	50	60	80	111	H+27	40	20		69.8	91	9	27					


- ① 可能出现螺孔M底孔贯穿的情况。

分离型




代码	类型	材质		表面处理	附件
		国标	相当		
GDF01	分离型	45	S45C	发黑	2个内六角圆柱头螺钉
GDF02		0Cr18Ni9	SUS304	喷细砂无电解镍	2个内六角圆柱头螺钉(不锈钢)
GDF06		LF2	A5052	喷细砂本色阳极氧化	



来图定制



- ① D30~50有4个附件内六角圆柱头螺钉。
② 如对防锈有要求，请优先选用不锈钢材质、铝合金材质或喷细砂无电解镍产品。



视角标准：第一视角

型号		H																L	H ₁	T	T ₁	S	W	L ₁	d	E	M	d ₂	d ₁	h	N	
代码	D																															
GDF01 GDF02 GDF06 GDF08	8	(10)	(15)	(20)	25	30	40																									
	10	(10)	(15)	(20)	25	30	40	50	60											23												
	12	(10)	(15)	(20)	25	30	40	50	60																							
	13	(15)	(20)	25	30	40	50	60																								
	15	(15)	(20)	25	30	40	50	60																								
	16	(15)	(20)	25	30	40	50	60																								
	20	(20)	25	30	40	50	60	80																								
	25	(20)	(25)	30	40	50	60	80																								
	30	(25)	30	40	50	60	80																									
	35	(25)	30	40	50	60	80																									
40		30	40	50	60	80																										
50		40	50	60	80																											

- ① 带()的H尺寸对应的螺孔M底孔贯通。 ② 可能出现螺孔M底孔贯穿的情况。

分离型

型号		H		
代码	D			
GDF01	8	10	15	20
GDF02	10	10	15	20

GDF02 — D8 — H15



未税价(元)

优惠价

数量	1~9	10~
价格	100%	另行报价



交货期

5



请按图示订货