

# 定位块/防脱落挡板/定位组件

直线导轨用

## 直线导轨用定位块




代码	类型	材质	表面处理
ICG41	直线导轨用定位块	S45C	无电解镀镍
ICG51	直线导轨用定位块	S45C	无电解镀镍



标准型  
ICG41



沉孔型  
ICG51



型号	代码	规格	L	A	B	H	C	d	D	h
ICG41	5	19	—	9	5.4	—	—	—	—	—
	6	21	—	11	6	—	—	—	—	—
ICG51	5	19	16	9	13.5	7	5.5	9.5	5.5	—
	6	21	18	11	15	7.5	6.5	11	6.5	—



请按图示订货

型号	代码	规格
ICG41	5	6

● 优惠价



未税价(元)

数量 1~9 10~

价格 100% 另行报价




数量1~49pcs



## 直线导轨用防脱落挡板

代码	类型	材质
ICE01	直线导轨用防脱落挡板	SUS304

规格：24



规格：28、33



型号	代码	规格	A	B	C	V
ICE01	24	20	13	14	4.5	
	28	27	16	19	6	
	33	30	20	22	7	



请按图示订货

型号	代码	规格	A
ICE01	24	20	20
ICE01	33	27	27



未税价(元)

● 优惠价

数量 1~9 10~

价格 100% 另行报价




数量1~49pcs

## 直线导轨用定位组件


代码	类型	材质	表面处理
ICG71	直线导轨用定位组件	S45C	无电解镀镍
ICG81	直线导轨用定位组件	SUS304	—




安装后尺寸







安装后尺寸



安装前尺寸



安装前尺寸



※6为使用短头螺栓时尺寸，如使用圆柱头内六角螺栓时为7.1。

型号	代码	M	(推荐)紧固扭矩 (N·m)	滑轨压紧力 (kN)
ICG71	4	M4	1.8	3.1
ICG81	5	M5	7.8	8.9



请按图示订货

型号	代码	M	紧固扭矩 (N·m)
ICG71	4	M4	1.8
ICG81	5	M5	7.8



未税价(元)

● 优惠价

数量 1~9 10~

价格 100% 另行报价



数量1~49pcs