




碟形弹簧

进口型

代码	类型	材质	表面处理	最大压缩量
J-FEN01	进口型	51CrV4	磷化黑	h×75%
J-FEN02		SUS304	—	

厚度t	负载容许差 (75%位移量时)
< 1.25	-7.5%~+25%
1.25~3	-7.5%~+15%
> 3~6	-5.0%~+10%
> 6~15	±5%



进口型

型号 代码	厚度 t	d	全位移 (h)	总高度 L	压缩量(F×75%)时荷重 J-FEN01 J-FEN02
J-FEN01	8	0.3	0.25	0.55	118 104
	0.4	4.2	0.2	0.6	210 184
	0.4	0.3	0.7		206 184
	10	0.5	0.25	0.75	325 290
	0.5	5.2	0.35	0.85	295 263
	0.7	6.2	0.3	1	660 592
	14	0.5	0.4	0.9	275 246
	0.8	7.2	0.3	1.1	795 713
	16	0.6	0.45	1.05	412 369
	0.9	8.2	0.35	1.25	1010 925
	18	0.7	0.5	1.2	569 510
	1	9.2	0.4	1.4	1275 1146
J-FEN02	20	0.8	0.55	1.35	±0.15 746 669
	1.1	10.2	0.45	1.55	±0.15 1520 1367
	0.8		0.65	1.45	±0.10 707 634
	22.5	1.2*	0.5	1.7	±0.15 1930 —
	1.25*	11.2		1.75	±0.15 — 1543

型号 代码	厚度 t	d	全位移 (h)	总高度 L	压缩量(F×75%)时荷重 J-FEN01 J-FEN02
J-FEN01	25	0.9	0.7	1.6	±0.10 864 775
	1.5	12.2	0.55	2.05	±0.15 2930 3176
	1		0.8	1.8	±0.10 1110 1014
	28	1.5	0.65	2.15	±0.15 2840 3088
	1.5	14.2		2.1	1910 —
	31.5	1.25*	0.9	2.15	±0.15 — 1543
	1.75	16.3	0.7	2.45	±0.15 3870 3794
	1.2*			2.2	1700 —
	35.5	1.25*	1	2.25	±0.15 — 1367
	2	18.3	0.8	2.8	±0.15 5190 4676
	40	1.5	1.15	2.65	±0.15 2620 2823
	2.25	20.4	0.9	3.15	±0.15 6500 5471
J-FEN02	45	1.75	1.3	3.05	±0.15 3650 3529
	2.5	22.4	1	3.5	±0.20 7720 6927
	50	2	1.4	3.4	±0.15 4760 4279
	3	25.4	1.1	4.1	±0.20 12000 10766

① 带*号规格仅适用于J-FEN01；带*号规格仅适用于J-FEN02。② 荷重为参考值。



请按图示订货

型号 代码	厚度 t
FEN01	10 0.5

FEN01-D8-t0.4



未税价(元)

数量	1~99	100~
价格	100%	另行报价



交货期
8