

头部安装万向型 · 反作用力固定型

精密型氮气弹簧

代码	类型	材质			表面处理			使用气体	使用温度	氮气弹簧公差标准	
		气缸筒	活塞杆	前端部	气缸筒	活塞杆	前端部			力值(N)	公差范围
J-FHJ22	头部安装万向型	STKM11A	S20C	Q235	烤漆(黑色亚光)	黑色渗氮	烤漆(黑色亚光)	N ₂	-20°C~60°C	≤100	-5/+15
										101~200	-10/+20
										201~400	-15/+30
										401~600	-20/+40
										601~800	-25/+50
										801~1000	-30/+60
										1001~1200	-35/+70
										>1200	-40/+80

前端形状F

前端形状M

前端形状N

前端形状U

视角标准：第一视角

代码	型号	规格	前端形状	最大长度 Lmax	最小长度 Lmin	行程	氮气弹簧反作用力(20°C)N		A	B	H			
							最大长度-10mm行程时	最大长度-(S)mm行程时 (S)						
J-FHJ22	15050A		F	246	196	50	49	64	15	6	139			
	15050B	98					127	40						
	15050C	147					178							
	15080A	49					69					70		
	15080B	98					127							
	15090A	49					66	80						
	15090B	98					130							
	15100A	49					64					90		
	15100B	98					132							
	15100C	147					204							
	18100A	196					255	90						
	18100B	294					382							
	18120A	196					269					110		
	18120B	294					403							
	18120C	392					537							
	18150A	196					265	140				18	8	321
	18150B	294					392							
	18180A	196					275							
	18180B	294					413							
	18180C	392					550							
	18200A	196					261	190						406
	18200B	196					390							
	22050A	196					265							
	22050B	294					396							
	22050C	392					528							
	22080A	196					273	70						190
	22080B	294					407							
	22080C	392					542							
	22080K	490					675	80						210
	22090A	294					402							
	22090B	490					659							
	22100A	198					275	90						226
	22100B	294					411							
	22100C	392					548							
	22120A	196					274	110						260
	22120B	294					402							
	22120C	392					539							
	22120K	490					672	120				22	10	280
	22130A	198					270							
	22130B	294					403							
22130C	392	536	140			316								
22150A	198	269												
22150B	294	402												
22150C	392	534	170			370								
22180A	196	269												
22180B	294	403												
22180C	392	537	190			406								
22200A	196	267												
22200B	294	400												
22200C	392	533	240			440								
22250A	196	304												
22250B	294	450												
22250C	392	600	140	27.4	12.5	332								
22150	401	568												
22090	215	322												
28100A	490	657	90			242								
28100B	588	787												
28100C	686	918												
28150A	490	657	140			422								
28150B	588	780												
28150C	686	920												
28200A	490	657	190			456								
28200B	588	789												
28200C	686	921												
28250A	490	725	240											
28250B	686	1019												

请按图示订货

型号	规格	前端形状
J-FHJ22	22150	M
J-FHJ22	22090	N

J-FHJ22-22150-M

● 优惠价

数量	1~4	5~
价格	100%	另行报价

未税价(元)

交货期

8