

# 无油线性滑板

## 尺寸选择型 · 沉孔型


铜合金/铸铁 线性滑板厚度20

代码	类型	线性滑板厚度	材质
OBJ21	尺寸选择型 沉孔型	20	高力黄铜(SP2)镶嵌固体润滑剂
OBX01			铸铁(FC250)镶嵌固体润滑剂
OBJ22			高力黄铜(SP2)镶嵌固体润滑剂
OBX02			铸铁(FC250)镶嵌固体润滑剂


W=28、38时仅纵向R为R2

滑动方向 →


W=28、38时仅纵向(L方向)




2孔




3孔



4孔



6孔



视角标准：第一视角

型号	W	L	安装孔	L <sub>1</sub>	
高力黄铜 OBJ21	28	75	2孔	45	
		100		50	
		125		75	
		150		100	
		200		150	
	58	250	200	3孔	300
		75	25		
		100	50		
		125	75		
		150	100		
铸铁 OBX01	75	150	2孔	100	
		200		150	
		250		200	
	100	300	3孔	100	
		100		50	
		125		75	
		150		100	
125	200	150	2孔	100	
		200		150	
		250		200	
		300		200	
		300		200	
	150	125	2孔	75	
		150		100	
		200		150	
		250		200	
		300		200	

型号	W	L	安装孔	L <sub>1</sub>	L <sub>2</sub>
高力黄铜 OBJ22	100	100	4孔	50	50
		125		75	
		150		100	
		200		150	
		250		200	
	125	300	6孔	200	125
		300A		125	
		125		75	
		125A		75	
		150		100	
铸铁 OBX02	125	150A	4孔	100	75
		200		150	
		200A		150	
		250		200	
		250A		200	
	150	300	6孔	200	125
		300A		125	
		350		200	
		350A		200	
		150		100	
200	200	4孔	150	100	
	250		200		
	300		250		
	300A		250		
	300A		125		



型号	W	L
OBJ21	28	75
	38	100

OBJ21 - W28 - L75



优惠价	数量	1~9	10~
未税价(元)	价格	100%	另行报价



交货期  
7

