


环形弹簧

代码	类型	材质	
		国标	相当
YAS01	环形弹簧	0Cr18Ni9	SUS304-WPB
YAS02			
YAS03			





用途：橡皮筋的功能、油封的弹簧以及其他用途。



无连接
YAS01



螺旋连接
YAS02



焊接连接
YAS03



无连接

型号	线径d	长度L
代码	D	
YAS01	3	500
	3	1000
	4	500
	4	1000
	5	500
	5	1000
	6	750
	6	1500
	8	750
	8	1500
	10	750
	10	1500

螺旋连接/焊接连接

型号	线径d	适用直径	初始张力(N)	弹簧常数 N/mm
代码	S	D		
螺旋连接 YAS02 焊接连接 YAS03	16	2	18~20	1.2
	16	2.5	18~20	1.3
	18	2*	20~22	1.2
	18	2.5	20~22	1.3
	20	2	22~25	1.2
	20	2.5	22~25	1.3
	25	2	28~31	1.2
	25	2.5	28~31	1.3
	30	2	33~38	1.2
	30	2.5	33~38	1.3
	35	2	39~44	1.2
	35	2.5	39~44	1.3
	40	2.5	44~51	1.3
	40	3	44~51	2.2
	50	2.5	55~64	1.3
	50	3	55~64	2.2
	60	2.5*	66~76	1.3
	60	3	66~76	2.2
	70	2.5*	77~89	1.3
	70	3	77~89	2.2
	85	2.5*	93~108	1.3
	85	3	93~108	2.2
	100	2.5	110~128	1.3
	100	3	110~128	2.2

① S值、初始张力、弹簧常数是加工成环形前的计算值①

带*规格仅适用YAS02。

无连接

型号	线径d	长度L
代码	D	
YAS01	3	500
YAS01	3	1000

YAS01-D3-d0.4-L500

螺旋连接

型号	线径d
代码	S
YAS02	16
YAS02	18

YAS02-S16-D2-d0.35



请按图示订货



优惠价	数量 1~19	20~
价格 100%	另行报价	

未税价(元)



交货期	3
-----	---