


代码	类型	材质		允许位移量	弹簧常数公差
		国标	相当		
Y-YUTT	外径基准不锈钢型 标准型	0Cr18Ni9	SUS304-WPB	L×(27~40)%	±10%



- ① 压紧长度为参考值，制作时会有少许差异。
- ② 使用次数：100万次。
- ③ 带( )的L规格两端均未进行磨削加工。



视角标准：第一视角

代码	型号		d	压紧长度	F max	允许负载 Nmax	弹簧常数 N/mm	
	D	L						
3	0.4	(5)	0.35	2.8	2	2.9	1.45	
		(10)	0.4	4.8	4	5.9	1.48	
		(15)	0.45	8.3	6	8.8	1.47	
		(20)		8.8				
		(25)		11.8				
	(30)	0.5	14	8	11.8	1.48		
	0.5	(5)	0.4	2.6	2	2.9	1.45	
		(10)	0.45	3.9	4	5.9	1.48	
		(15)	0.5	6	6	8.8	1.47	
		(20)	0.55	9.4	8	11.8	1.48	
(25)		0.6	14.4	10	14.7	1.47		
(30)			11.8					
4	0.4	(5)	0.45	2.6	2	2.9	1.45	
		(10)	0.5	3.6	4	5.9	1.48	
		(15)	0.6	7.5	6	8.8	1.47	
		(20)	0.65	10.7	10	14.7	1.47	
		(25)	0.7	15.4	12	17.7	1.48	
	(30)	14		20.6	1.47			
	0.5	(5)	0.5	2.4	2	3.9	1.95	
		(10)	0.6	4.2	4	7.8	1.95	
		(15)	0.7	7.4	6	11.8	1.97	
		(20)	0.75	10	8	15.7	1.95	
(25)		10		19.6				
5	0.4	(30)	±0.6	0.8	13.6	12	23.5	
		(35)	±0.7	0.85	17.5	14	27.5	
		(40)	±0.8	16	31.4	16	31.4	
		(45)	±0.9	0.9	23.4	18	35.3	
		(50)	±1	18	35.3			
	0.5	(60)	±1.2	1	41	24	47.1	
		(70)	±1.4	1	41	24	47.1	
		(10)	±0.5	0.75	5.3	4	7.8	1.95
		(15)	±0.7	0.75	5.3	6	11.8	1.97
		(20)	±0.5	0.9	10.4	8	15.7	1.95
6	0.4	(25)	±0.6	1	17	12	23.5	
		(30)	±0.7	1	17	14	27.5	
		(35)	±0.8	19.1	16	31.4		
		(40)	±0.8	19.1	16	31.4		
		(45)	±0.9	18	35.3			
	0.5	(50)	±1	1.1	25.3	20	39.2	
		(60)	±1.2	24	47.1			
		(70)	±1.4	1.2	39.6	28	54.9	
		(10)	±0.5	0.85	5.1	4	7.8	1.95
		(15)	±0.7	0.85	5.1	6	11.8	1.97
7	0.4	(20)	±0.75	1	9.5	8	15.7	
		(25)	±0.9	1	9.5	10	19.6	
		(30)	±0.9	1.1	14.3	12	23.5	
		(35)	±1.05	1.1	14.3	14	27.5	
		(40)	±0.8	1.1	14.3	16	31.4	
	0.5	(45)	±0.9	1.2	20.4	18	35.3	
		(50)	±1	20	39.2			
		(60)	±1.2	1.3	29.9	24	47.1	
		(70)	±1.4	1.4	43.4	24	47.1	

代码	型号		d	压紧长度	F max	允许负载 Nmax	弹簧常数 N/mm
	D	L					
8	0.4	(15)	±0.7	1	5.75	6	11.8
		(20)	±0.75	1.2	10.5	8	15.7
		(25)	±0.75	1.2	10.5	10	19.6
		(30)	±0.9	1.3	15	12	23.5
		(35)	±1.05	1.3	15	14	27.5
	0.5	(40)	±1.2	1.4	20.3	16	31.4
		(45)	±1.35	1.4	20.3	18	35.3
		(50)	±1	1.5	27.8	20	39.2
		(60)	±1.2	1.5	27.8	24	47.1
		(70)	±1.4	1.6	38.4	28	54.9
9	0.4	(80)	±1.6	1.6	38.4	32	62.8
		(15)	±0.7	1.2	7.2	6	11.8
		(20)	±0.75	1.3	9.1	8	15.7
		(25)	±0.75	1.3	9.1	10	19.6
		(30)	±0.9	1.4	12.3	12	23.5
	0.5	(35)	±1.05	1.5	16.5	14	27.5
		(40)	±1.2	1.6	21.6	16	31.4
		(45)	±1.35	1.6	21.6	18	35.3
		(50)	±1.5	1.7	28	20	39.2
		(60)	±1.8	1.7	28	24	47.1
10	0.43	(70)	±1.4	1.8	36	28	54.9
		(80)	±1.6	1.8	36	32	62.8
		(20)	±0.7	1.7	10.6	8	31.4
		(25)	±0.75	1.8	12.6	10	39.2
		(30)	±0.9	1.8	12.6	12	47.1
	0.5	(35)	±1.05	1.8	12.6	14	54.9
		(40)	±1.2	2	19	16	62.8
		(45)	±1.35	2	19	18	70.6
		(50)	±1.5	2.2	27.5	20	78.5
		(60)	±1.8	2.2	27.5	24	94.1
11	0.43	(70)	±1.4	2.3	34.5	28	109.8
		(80)	±1.6	2.4	40.8	32	125.5
		(20)	±0.7	1.7	10.6	8	31.4
		(25)	±0.75	1.8	12.6	10	39.2
		(30)	±0.9	1.8	12.6	12	47.1
	0.5	(35)	±1.05	1.8	12.6	14	54.9
		(40)	±1.2	2	19	16	62.8
		(45)	±1.35	2	19	18	70.6
		(50)	±1.5	2.2	27.5	20	78.5
		(60)	±1.8	2.2	27.5	24	94.1

- ① 允许位移量Fmax：表示弹簧允许压缩的最大长度，超出此压缩量使用弹簧会缩短。
- ② 允许负载Nmax：表示压缩Fmax的负载，单位N。
- ③ 弹簧常数N/mm=(Nmax)/(Fmax)。



请按图示订货

型号		
代码	D	L
Y-YUTT	4	5
Y-YUTT	D4	L5



未税价(元)

● 优惠价

数量	1~9	10~
价格	100%	另行报价