


波形弹性垫圈/防松垫圈

波形弹性垫圈


代码	类型	材质		表面处理	适用标准
		国标	相当		
TBN56	波形弹性垫圈	65Mn(弹簧钢)		发黑	GB/T 955-1987
TBN57		0Cr18Ni9	SUS304	—	



TBN56



TBN57



代码	型号	公称直径	d		D		h	H	
			min	max	min	max		min	max
(弹簧钢) TBN56	3	3.2	3.5	7.42	8		0.5	0.8	1.6
	4	4.3	4.6	8.42	9			1.0	2.0
	5	5.3	5.6	10.3	11			1.1	2.2
	6	6.4	6.76	11.3	12			1.3	2.6
	8	8.4	8.76	14.3	15			1.5	3.0
(SUS304) TBN57	10	10.5	10.93	20.16	21		1.0	2.1	4.2
	12	13	13.43	23.16	24		1.2	2.5	5.0
	14	15	15.43	27.16	28			3.0	5.9
	16	17	17.43	29	30		1.5	3.2	6.3
	18	19	19.52	33	34			3.3	6.5
	20	21	21.52	35	36		1.6	3.7	7.4
	24	25	25.52	43	44		1.8	4.1	8.2



请按图示订货

代码	型号
TBN56	4
TBN57	5
TBN56—4	



未税价(元)



优惠价	
数量	1~49 50~
价格	100% 另行报价



交货期	
	7


防松垫圈

代码	类型	材质		表面处理	适用标准
		国标	相当		
TBN61	防松垫圈	Q235	SS400	发黑	DIN 9250S(STL)
TBN65			达克罗		
TBN62		0Cr18Ni9	SUS304		
TBN63		022Cr17Ni12Mo2	SUS316L		




EX Example 使用示例

安装紧固前



安装紧固后



防松垫圈主要应用于一般振动载荷下的连接场景，其双面都增加了齿形纹，起到防滑和锁紧的作用，可以防止由振动导致的松动，比一般的弹簧垫圈具有更好的防松效果。



代码	型号	公称直径	d	D	t	h max	适用螺杆
(SS400) TBN61 TBN65	2	2.2	4	0.35	0.6	2	
	3	3.2	5.5	0.45	0.9	3	
	4	4.3	7	0.5	1	4	
	5	5.3	9	0.6	1.1	5	
	6	6.4	10		1.2	6	
	7	7.4	12	0.7	1.3	7	
	8	8.4	13	0.8	1.4	8	
	10	10.5	16	1	1.6	10	
	12	13	18	1.1	1.7	12	
	14	15	22	1.2	2	14	
	16	17	24	1.3	2.1	16	
	18	19	27	1.4	2.3	18	
	20	21	30	1.5	2.4	20	
	22	23	33	1.4	2.7	22	
	24	25.6	36	1.8	2.7	24	
	27	28.6	39	1.8	3.1	27	
	30	31.6	45	2	3.2	30	
	33	34	50	2.5	4	33	
	36	38	54	2.5	4.2	36	

代码	型号	公称直径	d	D	t	h max	适用螺杆
(SUS304) TBN62	3	3.2	5.5	0.5	0.95	3	
	4	4.3	7			4	
	5	5.3	9	0.7	1.2	5	
	6	6.4	10			6	
	8	8.4	13			8	
	10	10.5	16	1	1.6	10	
	12	13	18	1.3	1.85	12	
	14	15	22	1.5	2.3	14	
	16	17	24			16	
	20	21	30	1.8	2.8	20	
(SUS316L) TBN63	24	25.6	36	2	3.1	24	
	30	31.6	45	2.5	4.1	30	



请按图示订货

代码	型号
TBN61	3
TBN65	4
TBN61—3	



未税价(元)

优惠价

数量	1~49 50~
价格	100% 另行报价



TBN61

交货期	
	3



其余